

INDUSTRIAL COMPONENT DATA

PKZM0-0,25-C 229670 XTPRCP25BC1NL EATON ELECTRIC

Motor-protective circuit-breaker, 3p, Ir 0.16-0.25A, spring..

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM0-0,25-C



Manufacturer	EATON - MOELLER
MPN / Reference	PKZM0-0,25-C
Catalog number	XTPRCP25BC1NL
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-173758A9E1
Generated	2026-08-06

Product Overview

Motor-protective circuit-breaker, 3p, Ir=0.16-0.25A, spring clamp connection

Motor Protective Switch 3 poles Ir=0.16-0.25 A Connection To

Motor-protective circuit-breaker according to IEC/EN60947, 3 pole size PKZM0, with adjustable overload and non-delayed short-circuit release, phase failure sensitive, screw and snap fitting, with spring-cage terminals, cap installation dimension 45mm, rated operating voltage Ue 690V, degree of protection IP20, finger proof according to VDE 0106 T. 100, accessories: auxiliary contact, voltage release, contact module, clip plate

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

EL-Nummer (Norway)4315168Motor-protective circuit-breaker, 3p, Ir=0.16-0.25A, spring clamp connectionMotor-protective circuit-breaker according to IEC/EN60947, 3 pole size PKZM0, with adjustable overload and non-delayed short-circuit release, phase failure sensitive, screw and snap fitting, with spring-cage terminals, cap installation dimension 45mm, rated operating voltage Ue 690V, degree of protection IP20, finger proof according to VDE 0106 T. 100, accessories: auxiliary contact, voltage release, contact module, clip plateDelivery program

Product rangePKZM0 motor protective circuit-breakers up to 32 ABasic functionMotor protectionNotesAlso suitable for motors with efficiency class IE3.Connection techniqueSpring-loaded terminalsContact sequenceMax. motor ratingAC-3380 V 400 V 415 V [P]0.06 kWAC-3440 V [P]0.06 kWAC-3500 V [P]0.06 kWAC-3660 V 690 V [P]0.12 kWRated uninterrupted current [Iu]0.25 ASetting rangeOverload releases[Ir]0.16 - 0.25 Ashort-circuit release[Irm]max. [Irm]3.9 APhase-failure sensitivityIEC/EN 60947-4-1, VDE 0660 Part 102Explosion protection (according to ATEX 94/9/EC)? PTB 10, ATEX 3013,

Ex II(2) GD

Observe manual MN03402003Z-DE/EN. Notes Overload trigger: tripping class 10 A

Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height. Technical data

General Standards IEC/EN 60947, VDE 0660, UL, CSA Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Storage- 40 - 80 °C Ambient temperature Ope...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZM0-0,25-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.