

INDUSTRIAL COMPONENT DATA

PKZM0-0,63 072733 Y7-72733 EATON ELECTRIC

Motor-protective circuit-breaker, 3p, Ir 0.4-0.63A, screw connecti..

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM0-0,63



Manufacturer	EATON - MOELLER
MPN / Reference	PKZM0-0,63
Catalog number	Y7-72733
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-2D6F92664E
Generated	2026-08-05

Product Overview

Motor-protective circuit-breaker, 3p, Ir=0.4-0.63A, screw connection

Motor Protective Switch 3 poles Ir=0.4-0.63 A Connection To

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker, 0.12 kW, 0.4 - 0.63 A, Screw terminals

Motor-protective circuit-breaker according to IEC/EN60947, 3 pole size PKZM0, with adjustable overload and non-delayed short-circuit release, phase failure sensitive, screw and snap fitting, with screw terminal, cap installation dimension 45mm, rated operating voltage Ue 690V, degree of protection IP20, finger proof according to VDE 0106 T. 100, accessories: auxiliary contact, voltage release, contact module, clip plate

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZM0 Motor-protective circuit-breaker Catalog Number 072733 Model Code PKZM0-0,63 EAN 4015080727330 Product Length/Depth 76 mm Product Height 93 mm Product Width 45 mm Product Weight 0.246 kg Certifications UL

CE

CSA

UL 60947-4-1

CSA File No.: 165628

IEC/EN 60947

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

VDE 0660

IEC/EN 60947-4-1

UL File No.: E36332 Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)

Functions Motor protection

Phase failure sensitive Number of poles Three-pole General

Connection Screw terminals Explosion safety category for dust ATEX dust-ex-protection, PTB 10, ATEX 3013, Ex II(2) GD
Lifespan, electrical 100,000 operations Lifespan, mechanical 100,000 Operations Mounting position Can be snapped on to
IEC/EN 60715 top-hat rail with 7.5 or 15 mm height. Operating frequency 40 Operations/h Overvoltage category III Pollution
degree 3 Product category Motor protective circuit breaker Protection Finger and back-of-hand proof, Protection against
direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Shock resistance
25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Suitable for Branch circuit: Manual type E
if used with terminal, or suitable for group installations, (UL/CSA)

Also motors with efficiency class IE3 Temper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZM0-0,63 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.