

INDUSTRIAL COMPONENT DATA

PKE12/XTU-4 121732 Y7-121732 EATON ELECTRIC

Motor-protective circuit-breaker, 3p, Ir 1-4A, standard

Brand: EATON - MOELLER | Manufacturer Part Number: PKE12/XTU-4



Manufacturer	EATON - MOELLER
MPN / Reference	PKE12/XTU-4
Catalog number	Y7-121732
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-2676C9E9C3
Generated	2026-08-05

Product Overview

Motor-protective circuit-breaker, 3p, Ir=1-4A, standard

PKE12/XTU-4

Eaton Moeller® series PKE12 Motor-protective circuit-breaker, Complete device with standard knob, Electronic, 1 - 4 A, With overload release

Motor-protective circuit-breaker complete device (basic device and electronic control unit) according to IEC60947-4-1, electronic wide-range overload protection (4:1), phase-failure and unbalance protection, adjustable tripping class, high short-circuit breaking capacity, isolating function. Flexible adaptation of the motor-protective circuit's current range through interchangeable electronic release units. Expandable with auxiliary switch, voltage release, current limiter, door coupling handles. World-market device, ATEX accreditation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE System-protective circuit-breaker Catalog Number 121732 Model Code PKE12/XTU-4 EAN 4015081195428 Product Length/Depth 101 mm Product Height 102.5 mm Product Width 45 mm

Product Weight 0.42 kg Compliances CE Marked Certifications CSA Std. C22.2 No. 14-10

UL 508

EN 60947-4-1

IEC 60947-4-1

VDE

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-4-1

IEC/EN 60947

CSA Class No.: 3211-05

UL 60947-4-1

CSA

CSA File No.: 165628

UL

UL Category Control No.: NLRV

UL File No.: E36332

VDE 0660

CE Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures. Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) Fitted with: Standard knob Functions Motor protection for heavy starting duty

Phase failure sensitive

Overload release

Motor protection Number of poles Three-pole General

Current flow times - min 500 (Class 5) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

900 (Class 15) AC-4 cycle operation, Main conducting paths

1000 (Class 20) AC-4 cycle operation, Main conducting paths

700 (Class 10) AC-4 cyc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE12/XTU-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.