

INDUSTRIAL COMPONENT DATA

PKZM4-58 222394 Y7-222394 EATON ELECTRIC

Motor-protective circuit-breaker, 3p, Ir 50-58A, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM4-58



Manufacturer	EATON - MOELLER
MPN / Reference	PKZM4-58
Catalog number	Y7-222394
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-FE35FD3149
Generated	2026-08-05

Product Overview

Motor-protective circuit-breaker, 3p, Ir=50-58A, screw connection

PKZM4-58

Eaton Moeller® series PKZM4 Motor-protective circuit-breaker, Ir= 50 - 58 A, Screw terminals, Terminations: IP00

PKZM4-58

Motor-protective circuit-breaker according to IEC/EN60947, 3 pole size PKZM4, with adjustable overload and non-delayed short-circuit release, phase failure sensitive, screw and snap fitting, rated operating voltage Ue 690V, degree of protection IP20, finger proof according to VDE 0106 T. 100, accessories: auxiliary contact, voltage release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZM4 Motor-protective circuit-breaker Catalog Number 222394 Model Code PKZM4-58 EAN 4015082223946 Product Length/Depth 160 mm Product Height 140 mm Product Width 55 mm Product Weight 1.136 kg Certifications CSA Class No.: 3211-05

IEC/EN 60947-4-1

CSA File No.: 165628

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

VDE 0660

CE

CSA

IEC/EN 60947

UL File No.: E36332

UL

UL 60947-4-1 Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)

Functions Motor protection

Phase failure sensitive Number of poles Three-pole General

Explosion safety category for dust ATEX dust-ex-protection, PTB 10, ATEX 3012, Ex II(2) G Lifespan, electrical 30,000 operations (at 400V, AC-3) Lifespan, mechanical 30,000 Operations (Main conducting paths) Mounting position Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height. Operating frequency 40 Operations/h Overvoltage category III Pollution degree 3 Product category Motor protective circuit breaker Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Suitable for Also motors with efficiency class IE3

Branch circuit: Manual type E if used with terminal, or suitable for group installations, (UL/C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZM4-58 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.