

INDUSTRIAL COMPONENT DATA

PKE32/XTU-32 121734 Y7-121734 EATON ELECTRIC

Motor-protective circuit-breaker, 3p, Ir 8-32A, standard

Brand: EATON - MOELLER | Manufacturer Part Number: PKE32/XTU-32



Manufacturer	EATON - MOELLER
MPN / Reference	PKE32/XTU-32
Catalog number	Y7-121734
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-C2C923DF88
Generated	2026-08-06

Product Overview

Motor-protective circuit-breaker, 3p, Ir=8-32A, standard

PKE32/XTU-32

Eaton Moeller® series PKE32 Motor-protective circuit-breaker, Complete device with standard knob, Electronic, 8 - 32 A, 32 A, With overload release, Screw terminals

Motor-protective circuit-breaker complete device (basic device and electronic control unit) according to IEC60947-4-1, electronic wide-range overload protection (4:1), phase-failure and unbalance protection, adjustable tripping class, high short-circuit breaking capacity, isolating function. Flexible adaptation of the motor-protective circuit's current range through interchangeable electronic release units. Expandable with auxiliary switch, voltage release, current limiter, door coupling handles. World-market device, ATEX accreditation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Electronic Circuit Breakers
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE System-protective circuit-breaker Catalog Number 121734 Model Code

PKE32/XTU-32 EAN 4015081195442 Product Length/Depth 101 mm Product Height 102.5 mm Product Width 45 mm

Product Weight 0.436 kg Certifications CE

CSA

IEC/EN 60947-4-1

IEC/EN 60947

CSA Class No.: 3211-05

CSA File No.: 165628

CSA-C22.2 No. 60947-4-1-14

UL

UL File No.: E36332

UL Category Control No.: NLRV

VDE 0660

UL 60947-4-1 Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures. Features & Functions

Actuator type Turn button Features Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) Fitted with: Standard knob Functions Motor protection for heavy starting duty

Motor protection

Overload release Number of poles Three-pole General

Current flow times - min 700 (Class 10) AC-4 cycle operation, Main conducting paths

900 (Class 15) AC-4 cycle operation, Main conducting paths

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

500 (Class 5) AC-4 cycle operation, Main conducting paths

1000 (Class 20) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor). Cut-out periods - min ≤ 500 ms, main conducting paths, AC-4 cycle opera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE32/XTU-32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.