


INDUSTRIAL COMPONENT DATA

PKZM0-2,5-C-GVP2 100805 XTPRC2P5BC1NLBP2 EATON ELECTRIC Motor-protective circuit-breaker, 3p, Ir 1.6-2.5A, s..

Brand: EATON - MOELLER | Manufacturer Part Number: PKZM0-2,5-C-GVP2



Manufacturer	EATON - MOELLER
MPN / Reference	PKZM0-2,5-C-GVP2
Catalog number	XTPRC2P5BC1NLBP2
Category	Motor protection circuit-breaker
Minimum order	27 Pcs
Document ID	EO-2C5F90B35A
Generated	2026-08-03

Product Overview

Motor-protective circuit-breaker, 3p, Ir=1.6-2.5A, spring clamp connection, large packaging

Motor Protection Switch 3 poles Ir=1.6-2.5 A Connection to

Motor-protective circuit-breaker in environmentally friendly large packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

Motor-protective circuit-breaker, 3p, Ir=1.6-2.5A, spring clamp connection, large packaging Motor-protective circuit-breaker in environmentally friendly large packaging Delivery program

Product range PKZM0 motor protective circuit-breakers up to 32 A Basic function Motor protection Notes Also suitable for motors with efficiency class IE3.

IE3-ready devices are identified by the logo on their packaging. Connection technique Spring-loaded terminals Contact sequence Max. motor rating AC-3220 V 230 V 240 V [P] 0.37 kW AC-3380 V 400 V 415 V [P] 0.75 kW AC-3440 V [P] 1.1 kW AC-3500 V [P] 1.1 kW AC-3660 V 690 V [P] 1.5 kW Rated uninterrupted current [Iu] 2.5 A Setting range Overload releases[Ir] 1.6 - 2.5 A short-circuit release[Irm]max. [Irm] 38.8 A Phase-failure sensitivity IEC/EN 60947-4-1, VDE 0660 Part 102 Explosion protection (according to ATEX 94/9/EC) ? PTB 10, ATEX 3013, Ex II(2) GD

Observe manual MN03402003Z-DE/EN. Notes Overload trigger: tripping class 10 A

Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height. Technical data

General Standards IEC/EN 60947, VDE 0660,UL, CSA Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperatureStorage - 40 - 80 °C Ambient temperatureOpen -25 - +55 °C

Ambient temperature Enclosed - 25 - 40 °C Mounting position Direction of incoming supply as required Degree of protection Device IP20 Degree of protection Terminations IP00 Protection against direct contact when actuat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZM0-2,5-C-GVP2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.