


## INDUSTRIAL COMPONENT DATA

# BPZ-NZM1X-600-MV-W 108363 EATON ELECTRIC Mounting plate & front plate for H x W 200 x 600 mm, NZM1, vertical..

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-NZM1X-600-MV-W



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | EATON - MOELLER                       |
| MPN / Reference | BPZ-NZM1X-600-MV-W                    |
| Catalog number  | 108363                                |
| Category        | Mounting plate for distribution board |
| Minimum order   | 1 Pcs                                 |
| Document ID     | EO-43DAC20943                         |
| Generated       | 2026-08-05                            |

## Product Overview

Mounting plate & front plate for H x W = 200 x 600 mm, NZM1, vertical, for multiple mounting, white BPZ-NZM.X-..-MV mounting kit for NZM multiple mounting, width 600 mm, height 200mm, for mounting multiple NZM units in a vertical position. Max. 4 NZM1 3-pole/3 NZM1 4-pole, sheet steel front plate, powder-spray painted, RAL 9016, 2-mm PVC insert, sheet steel mounting plate (2 mm), galvanized. Metal front plates in electrical contact with enclosure, suitable for surface-mounted enclosures and floor standing distribution boards. Equipment supplied: 1 mounting plate, 1 front plate, various mounting accessories, if more than one type of circuit-breaker is used, spacer NZM1/2-XAB must be used.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                              |
|--------------|------------------------------|
| Catalog path | EATON - MOELLER > Enclosures |
|--------------|------------------------------|

## Additional Product Information

Fuse-link, LV, 600 A, AC 600 V, 64 x 203 mm, J, UL, fast acting Fuse, fuse-link, low voltage, 600 A, AC 600 V, 64 x 203 mm, Class J, UL, fast acting, ideal for critical industrial or commercial applications that have specific current limitation requirements. Breaking capacity 200 kA [ Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 600 A Rated voltage AC 600 V Size 64 x 203 mm Utilization category J Breaking Capacity 200 kA usable for size/applications ideal for critical industrial or commercial applications that have specific current limitation requirements Release characteristic [class] fast-acting Standard/Approval UL , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]) [AFZ800015]) Construction size Other Rated current 600 A Rated voltage 600 V Voltage type AC Rated switching capacity

200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No ]

ETIM for 108363 Power distribution systems (EC000213)

Feature Name

Feature Value

Height (EF000040)

205 mm

Width (EF000008)

525 mm

Material (EF002169)

Steel

Surface protection (EF000139)

Galvanised

Perforated (EF000115)

Yes

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-NZM1X-600-MV-W with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.