

INDUSTRIAL COMPONENT DATA

BPZ-NZM2X-400-MV 108357 EATON ELECTRIC Mounting plate & front plate for H x W 300 x 400 mm, NZM2, vertical, ..

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-NZM2X-400-MV



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-NZM2X-400-MV
Catalog number	108357
Category	Mounting plate for distribution board
Minimum order	1 Pcs
Document ID	EO-8F3CF2A32A
Generated	2026-08-04

Product Overview

Mounting plate & front plate for H x W = 300 x 400 mm, NZM2, vertical, for multiple mounting BPZ-NZM.X-..-MV mounting kit for NZM multiple mounting, width 400 mm, height 300mm, for mounting multiple NZM units in a vertical position. Max. 2 NZM2 3-pole/1 NZM2 4-pole, sheet steel front plate, powder-spray painted, RAL 7035, 2-mm PVC insert, sheet steel mounting plate (2 mm), galvanized. Metal front plates in electrical contact with enclosure, suitable for surface-mounted enclosures and floor standing distribution boards. Equipment supplied: 1 mounting plate, 1 front plate, various mounting accessories, if more than one type of circuit-breaker is used, spacer NZM1/2-XAB must be used.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

circuit limiter, low voltage, 400 A, DC 80 V, 22.2 x 81 mm, UL Fuse, circuit limiter, low voltage, 400 A, DC 80 V, 22.2 x 81 mm, UL, fork-lift trucks, marine and other battery-operated systems, Breaking Capacity 2.7 kA, Optional accessories fuse-block 4164 [Delivery program

Product range Fuse Basic function circuit limiter Field of application low voltage Rated current [I] 400 A Rated voltage DC 80 V Size 22.2 x 81 mm Breaking Capacity 2.7 kA usable for size/applications fork-lift trucks, marine and other battery-operated systems Standard/Approval UL Optional accessories fuse-block 4164 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size Other Rated current 400 A Rated voltage 80 V Voltage type DC Voltage type DC Rated switching capacity 2.7 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL)

No]

ETIM for 108357 Power distribution systems (EC000213)

Feature Name

Feature Value

Height (EF000040)

305 mm

Width (EF000008)

325 mm

Material (EF002169)

Steel

Surface protection (EF000139)

Galvanised

Perforated (EF000115)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-NZM2X-400-MV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.