

INDUSTRIAL COMPONENT DATA

BPZ-NZM2X-600-MV 108358 EATON ELECTRIC Mounting plate & front plate for H x W 300 x 600 mm, NZM2, vertical, ..

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-NZM2X-600-MV



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-NZM2X-600-MV
Catalog number	108358
Category	Mounting plate for distribution board
Minimum order	1 Pcs
Document ID	EO-A8AD9F18BF
Generated	2026-08-05

Product Overview

Mounting plate & front plate for H x W = 300 x 600 mm, NZM2, vertical, for multiple mounting BPZ-NZM.X-..-MV mounting kit for NZM multiple mounting, width 600 mm, height 300mm, for mounting multiple NZM units in a vertical position. Max. 3 NZM2 3-pole/3 NZM2 4-pole, sheet steel front plate, powder-spray painted, RAL 7035, 2-mm PVC insert, sheet steel mounting plate (2 mm), galvanized. Metal front plates in electrical contact with enclosure, suitable for surface-mounted enclosures and floor standing distribution boards. Equipment supplied: 1 mounting plate, 1 front plate, various mounting accessories, if more than one type of circuit-breaker is used, spacer NZM1/2-XAB must be used.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Fuse-link, LV, 600 A, AC 600 V, 64 x 203 mm, J, UL, fast acting Fuse, fuse-link, low voltage, 600 A, AC 600 V, 64 x 203 mm, Class J, UL, fast acting, ideal for critical industrial or commercial applications that have specific current limitation requirements. Breaking capacity 200 kA [Delivery program
Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 600 A Rated voltage AC 600 V Size 64 x 203 mm Utilization category J Breaking Capacity 200 kA usable for size/applications ideal for critical industrial or commercial applications that have specific current limitation requirements Release characteristic [class] fast-acting
Standard/Approval UL , Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015]) Construction size Other Rated current 600 A Rated voltage 600 V Voltage type AC Rated switching capacity

200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No]

ETIM for 108358 Power distribution systems (EC000213)

Feature Name

Feature Value

Height (EF000040)

305 mm

Width (EF000008)

525 mm

Material (EF002169)

Steel

Surface protection (EF000139)

Galvanised

Perforated (EF000115)

Yes

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-NZM2X-600-MV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.