

INDUSTRIAL COMPONENT DATA

XVTL-IZM58-12 115156 EATON ELECTRIC Mounting plate for IZM58, W 1200mm

Brand: EATON - MOELLER | Manufacturer Part Number: XVTL-IZM58-12



Manufacturer	EATON - MOELLER
MPN / Reference	XVTL-IZM58-12
Catalog number	115156
Category	Mounting plate for distribution board
Minimum order	1 Pcs
Document ID	EO-F18BD4B28E
Generated	2026-08-04

Product Overview

Mounting plate for IZM58, W=1200mm

IZM58 mounting plate, width 1200 mm, mounting material, galvanized sheet steel, for mounting IZM58 units

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Fuse-link, low voltage, 12 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay Fuse, Fuse-link, low voltage, 12 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay, cylindrical, size-rejecting, fusible branch panelboards, HVAC branch circuit protection, UL 248-5, Breaking Capacity 100 kA, time-delay 12 seconds (minimum) at 200% of rated current [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 12 A Rated voltage AC 600 V DC 170 V Size 33.3 x 10.4 mm Utilization category G Description size-rejecting Breaking Capacity 100 kA usable for size/applications fusible branch panelboards, HVAC branch circuit protection Release characteristic [class] time-delay Standard/Approval UL

CSA Shape cylindrical Standards/Regulations UL 248-5 Time delay time-delay 12 seconds (minimum) at 200% of rated current , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013]) Size Other Rated voltage 600 - 600 V Rated voltage Other Voltage type AC/DC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 12 A With striker No Release characteristic G Breaking capacity 100

kA]

ETIM for 115156 Power distribution systems (EC000213)

Feature Name

Feature Value

Height (EF000040)

115 mm

Wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XVTL-IZM58-12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.