

INDUSTRIAL COMPONENT DATA

MFD-TS-144 274090 0004519729 EATON ELECTRIC Mounting rail for mounting MFD-CP8/CP10 with MFD-80 and easy-exp..

Brand: EATON - MOELLER | Manufacturer Part Number: MFD-TS-144



Manufacturer	EATON - MOELLER
MPN / Reference	MFD-TS-144
Catalog number	0004519729
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-FCD509B39F
Generated	2026-08-05

Product Overview

Mounting rail for mounting MFD-CP8/CP10 with MFD-80 and easy-expansion (2HP)

DIN rail for connection of extensions to MFD-CP8/CP10; 144 mm

Mounting rail with cutout, for fixing of MFD-CP8/CP10, cutout allows the snapping of the display and operating unit MFD-80... in MFD-CP8/CP10, with a length of 142.5 mm, sufficient space remains to enable fastening an extension with 2 space units, corresponds to IEC/EN 60715

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

EL-Nummer (Norway)4519729Mounting rail for mounting MFD-CP8/CP10 with MFD-80 and easy-expansion (2HP)Mounting rail with cutout, for fixing of MFD-CP8/CP10, cutout allows the snapping of the display and operating unit MFD-80... in MFD-CP8/CP10, with a length of 142.5 mm, sufficient space remains to enable fastening an extension with 2 space units, corresponds to IEC/EN 60715Delivery program
Product rangeMulti-function-display MFD-TitanFor use witheasy200Information relevant for export to North AmericaUL/CSA certification not required
Design verification as per IEC/EN 61439
Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+55 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion

resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heatMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat an...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MFD-TS-144 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.