

INDUSTRIAL COMPONENT DATA

MP2 SURFACE 3H MTD OPEN C/W CGL MP2SO3HCGL

EATON ELECTRIC MP2 SURFACE 3H MTD OPEN C/W CGL

Brand: EATON - MOELLER | Manufacturer Part Number: MP2 SURFACE 3H MTD OPEN C/W CGL



Manufacturer	EATON - MOELLER
MPN / Reference	MP2 SURFACE 3H MTD OPEN C/W CGL
Catalog number	MP2SO3HCGL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-A808608461
Generated	2026-08-01

Product Overview

MP2 SURFACE 3H MTD OPEN C/W CGL

Eaton Micropoint 2 Surface, Safety lighting, Open area, CGLine + technology, LED, Maintained / Non-Maintained operation, IP44, 144lm, 3 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Central Battery System
--------------	--

Additional Product Information

ETIM for MP2SO3HCGL Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Ceiling surface mounting

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)
Peripheral (individual battery)
Battery technology (EF004351)
NiCd
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
1
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
1
Housing material (EF001596)
Plastic
Housing colour (EF000136)
White
Material cover (EF004284)
Other
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
220 V
Type of control gear (EF000381)
LED driver constant current
Light distributor (EF012170)
Focal lens
Degree of protection (IP) (EF005474)
IP44
Impact strength (EF004293)
IK04
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
Yes
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
2.5 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
144 lm
Luminous flux in standby mode (EF011954)
144 lm
Colour temperature (EF009346)
6200 K
Power factor (EF025740)

0.5

Nominal operation time (EF012518)

3 h

Width (EF000008)

170 mm

Height/depth (EF001456)

50 mm

Length (EF001438)

170 mm

Buil...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MP2 SURFACE 3H MTD OPEN C/W CGL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.