

INDUSTRIAL COMPONENT DATA

MP2E3HCGL EATON ELECTRIC MICROPPOINT2 3H MTD EXHAUST C/W CGL

Brand: EATON - MOELLER | Manufacturer Part Number: MP2E3HCGL



Manufacturer	EATON - MOELLER
MPN / Reference	MP2E3HCGL
Catalog number	10000
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-EED8F3BF76
Generated	2026-08-03

Product Overview

MICROPPOINT2 3H MTD ESCAPE C/W CGL

Eaton Micropoint 2, Safety lighting, Escape route, CGLine + technology, LED, Maintained / Non-Maintained operation, IP44, 148lm, 3 hour duration, Recessed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Central Battery System
--------------	--

Additional Product Information

ETIM for MP2E3HCGL Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Built-in

Suitable for labelling type (EF001277)

Other

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)
Peripheral (individual battery)
Battery technology (EF004351)
NiCd
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
1
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
1
Housing material (EF001596)
Plastic
Housing colour (EF000136)
White
Material cover (EF004284)
Other
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
230 V
Type of control gear (EF000381)
Not required
Light distributor (EF012170)
Focal lens
Degree of protection (IP) (EF005474)
IP44
Impact strength (EF004293)
IK03
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
Yes
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
5 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
148 lm
Luminous flux in standby mode (EF011954)
148 lm
Colour temperature (EF009346)
6200 K
Power factor (EF025740)

0.72

Nominal operation time (EF012518)

3 h

Height/depth (EF001456)

75 mm

Outer diameter (EF000015)

90 mm

Built-in height/depth (EF023518)

63 mm

Built-in diamet...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MP2E3HCGL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.