

INDUSTRIAL COMPONENT DATA

MSC-DE-4-M17(24VDC) 168803 Y7-168803 EATON ELECTRIC Electronic control relay, rated operating voltage 24VDC,..

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-DE-4-M17(24VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-DE-4-M17(24VDC)
Catalog number	Y7-168803
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-DB9AAF589B
Generated	2026-08-05

Product Overview

Electronic control relay, rated operating voltage 24VDC, 8 digital inputs 24VDC, 2 inputs can be used as analog inputs, 4 transistor outputs 24VDC, keyboard, LCD display, time switch, menu also available in Cyrillic

MSC-DE-4-M17(24VDC)

DOL starter, 380 V 400 V 415 V: 1.5 kW, Iq= 100 kA, Ir= 1 - 4 A, 24 V DC, DC Voltage, Screw terminals

DOL starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 1.5 kW, Motor ratings Motor rating AC-3 500 V: P= 2.2 kW, Motor ratings Rated operational current AC-3 500 V: Ie= 4 A, Motor ratings Rated conditional short-circuit current 500 V: Iq= 50 kA, Setting range of overload releases: Ir= 1 - 4 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 24 V DC, DC Voltage, Standards: IEC/EN 60947-4-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

DOL starter, 380 V 400 V 415 V: 1.5 kW, Iq= 100 kA, Ir= 1 - 4 A, 24 V DC, DC Voltage, Screw terminalsDOL starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 1.5 kW, Motor ratings Motor rating AC-3 500 V: P= 2.2 kW, Motor ratings Rated operational current AC-3 500 V: Ie= 4 A, Motor ratings Rated conditional short-circuit current 500 V: Iq= 50 kA, Setting range of overload releases: Ir= 1 - 4 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 24 V DC, DC Voltage, Standards: IEC/EN 60947-4-1, VDE 0660Delivery program
Basic functionDOL starters (complete devices)Basic deviceMSCNotesAlso suitable for motors with efficiency class IE3.

IE3-ready devices are identified by the logo on their packaging. Connection technique Screw terminals Connection to SmartWire-DT no Motor ratings Motor rating [P] AC-3380 V 400 V 415 V [P] 1.5 kW Motor rating [P] AC-3500 V [P] 2.2 kW Rated operational current AC-3380 V 400 V 415 V [I_e] 3.6 A Rated operational current AC-3500 V [I_e] 4 A Rated short-circuit current 380 - 415 V [I_q] 100 kA Rated conditional short-circuit current 500 V [I_q] 50 kA Setting range Setting range of overload releases [I_r] 1 - 4 A Coordination Type of coordination "1" Type of coordination "2" Contact sequence Actuating voltage 24 V DC DC Voltage Motor-protective circuit-breakers PKE12/XTU-4 Type Contactor DILM17-10(...) Pa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-DE-4-M17(24VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.