

INDUSTRIAL COMPONENT DATA

MSC-DM-0,63-M7(24VDC)MSFA 191104 Y7-191104 EATON ELECTRIC DOL starter on feeder system adapter, 3-pole, 0.18..

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-DM-0,63-M7(24VDC)MSFA



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-DM-0,63-M7(24VDC)MSFA
Catalog number	Y7-191104
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-1571AD1E3E
Generated	2026-08-05

Product Overview

DOL starter on feeder system adapter, 3-pole, 0.18 kW/400 V/AC-3, 100 kA, DC operated

MSC-DM-0,63-M7(24VDC)MSFA

Eaton Moeller® series MSC-DM DOL starter, 380 V 400 V 415 V: 0.12, 0.18 kW, Ir= 0.4 - 0.63 A, 24 V DC, DC voltage

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series MSC-DM DOL starter Catalog Number 191104 Model Code

MSC-DM-0,63-M7(24VDC)MSFA EAN 4015081916023 Product Length/Depth 115 mm Product Height 180 mm Product Width 45 mm Product Weight 0.724 kg Certifications UL 508 (on request)

CSA-C22.2 No. 14 (on request) Features & Functions

Fitted with: Short-circuit release Functions Temperature compensated overload protection General

Class CLASS 10 A Connection Screw terminals Connection to SmartWire-DT No Coordination type 2 Degree of protection IP20

NEMA Other Model IEC starter Mounting method Motor starter Feeder System Number of auxiliary contacts (normally

closed contacts) 0 Number of auxiliary contacts (normally open contacts) 1 Overload release current setting - min 0.4 A

Overload release current setting - max 0.63 A Overvoltage category III Pollution degree 3 Rated impulse withstand voltage

(Uimp) 6000 V AC Suitable for Also motors with efficiency class IE3 Type Starter with Bi-Metal release Voltage type DC
Climatic environmental conditions

Altitude Max. 2000 m Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Electrical
rating

Rated operational current (Ie) 0.6 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V 0.63 A Rated operational
power at AC-3, 220/230 V, 50 Hz 0.09 kW Rated operational power at AC-3, 380/400 V, 50 Hz 0.18 kW Rated operational
voltage 230 - 415 V AC Short-circuit rating

Rated conditional short-circuit cur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-DM-0,63-M7(24VDC)MSFA with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.