

INDUSTRIAL COMPONENT DATA

MSC-DM-1,6-M7(230V50HZ)/MSFA 191118 XTSC1P6B007BMFNL-FS EATON ELECTRIC DOL starter on feeder system adapter,...

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-DM-1,6-M7(230V50HZ)/MSFA



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-DM-1,6-M7(230V50HZ)/MSFA
Catalog number	XTSC1P6B007BMFNL-FS
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-9697DF39A8
Generated	2026-08-04

Product Overview

DOL starter on feeder system adapter, 3-pole, 0.55 kW/400 V/AC-3, 100 kA

Motor starter direct on system of power supply; 3-pole; 0.55 kW / 400 V / AC-3; 100 kA; 230 V 50 Hz

DOL starter, 380 V 400 V 415 V: 0.37, 0.55 kW, Ir= 1 - 1.6 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage

DOL starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 0.37, 0.55 kW, Setting range of overload releases: Ir= 1 - 1.6 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

DOL starter, 380 V 400 V 415 V: 0.37, 0.55 kW, Ir= 1 - 1.6 A, 230 V 50 Hz, 240 V 60 Hz, AC voltageDOL starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 0.37, 0.55 kW, Setting range of overload releases: Ir= 1 - 1.6 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request)Delivery program

Basic functionDOL starters (complete devices)Basic deviceMSCNotesAlso suitable for motors with efficiency class IE3. IE3-ready devices are identified by the logo on their packaging.Connection to SmartWire-DTnoMotor ratingsMotor rating

[P]AC-3380 V 400 V 415 V [P]0.37

0.55 kW Rated operational current AC-3380 V 400 V 415 V [Ie]1.1

1.5 A Rated short-circuit current 380 - 415 V [Iq]100 kA Setting range Setting range of overload releases [I_r]1 - 1.6

A Coordination Type of coordination "1"

Type of coordination "2" Contact sequence Actuating voltage 230 V 50 Hz, 240 V 60 Hz AC voltage Motor-protective circuit-breakers PKZM0-1,6 Type Contactor DILM7-10(...) Part no. DOL starter wiring set

Mechanical connection element and electrical electric contact module PKZM0-XDM15ME Type Notes The DOL starters (complete units) consist of a PKZM0 motor protective circuit breaker and a DILM contactor. These combinations are mounted on the busbar adapt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-DM-1,6-M7(230V50HZ)/MSFA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.