

## INDUSTRIAL COMPONENT DATA

# MSC-DM-2,5-M7(24VDC)/MSFA 191107 Y7-191107 EATON ELECTRIC DOL starter on feeder system adapter, 3-pole, 0.75..

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-DM-2,5-M7(24VDC)/MSFA



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | EATON - MOELLER                         |
| MPN / Reference | MSC-DM-2,5-M7(24VDC)/MSFA               |
| Catalog number  | Y7-191107                               |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-9ADC525D9E                           |
| Generated       | 2026-08-05                              |

## Product Overview

DOL starter on feeder system adapter, 3-pole, 0.75 kW/400 V/AC-3, 150 kA, DC operated

MSC-DM-2,5-M7(24VDC)/MSFA

Eaton Moeller® series MSC-DM DOL starter, 380 V 400 V 415 V: 0.75 kW, Ir= 1.6 - 2.5 A, 24 V DC, DC voltage

MSC-DM-2,5-M7(24VDC)/MSFA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

## Additional Product Information

General specifications

Product Name Eaton Moeller® series MSC-DM DOL starter Catalog Number 191107 Model Code

MSC-DM-2,5-M7(24VDC)/MSFA EAN 4015081916054 Product Length/Depth 115 mm Product Height 180 mm Product Width 45 mm Product Weight 0.767 kg Certifications UL 508 (on request)

CSA-C22.2 No. 14 (on request) Features & Functions

Fitted with: Short-circuit release Functions Temperature compensated overload protection General

Class CLASS 10 A Connection Screw terminals Connection to SmartWire-DT No Coordination type 2 Degree of protection IP20

NEMA Other Model IEC starter Mounting method Motor starter Feeder System Number of auxiliary contacts (normally closed contacts) 0 Number of auxiliary contacts (normally open contacts) 1 Overload release current setting - min 1.6 A

Overload release current setting - max 2.5 A Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (Uimp) 6000 V AC Suitable for Also motors with efficiency class IE3 Type Starter with Bi-Metal release Voltage type DC Climatic environmental conditions

Altitude Max. 2000 m Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Electrical rating

Rated operational current (Ie) 1.9 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V 2.5 A Rated operational power at AC-3, 220/230 V, 50 Hz 0.37 kW Rated operational power at AC-3, 380/400 V, 50 Hz 0.75 kW Rated operational voltage 230 - 415 V AC Short-circuit rating

Rated conditional short-circuit curre...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-DM-2,5-M7(24VDC)/MSFA with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.