


INDUSTRIAL COMPONENT DATA

MSC-DM-4-M7(230V50HZ)/MSFA 191120 XTSC004B007BMFNL-FS EATON ELECTRIC DOL starter on feeder system adapter, 3..

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-DM-4-M7(230V50HZ)/MSFA



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-DM-4-M7(230V50HZ)/MSFA
Catalog number	XTSC004B007BMFNL-FS
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-5A2CB8141A
Generated	2026-08-04

Product Overview

DOL starter on feeder system adapter, 3-pole, 1.5 kW/400 V/AC-3, 150 kA

Motor starter direct on system of power supply; 3-pole; 1.5 kW / 400 V / AC-3; 150 kA; 230 V 50 Hz

DOL starter, 380 V 400 V 415 V: 1.1, 1.5 kW, Ir= 2.5 - 4 A, 230 V 50 Hz, 240 V 60 Hz, AC voltage

DOL starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 1.1, 1.5 kW, Setting range of overload releases: Ir= 2.5 - 4 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

DOL starter, 380 V 400 V 415 V: 1.1, 1.5 kW, Ir= 2.5 - 4 A, 230 V 50 Hz, 240 V 60 Hz, AC voltageDOL starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor ratings Motor rating AC-3 380 V 400 V 415 V: P= 1.1, 1.5 kW, Setting range of overload releases: Ir= 2.5 - 4 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: UL 508 (on request), CSA C 22.2 No. 14 (on request)

General specificationsProduct nameEaton Moeller® series MSC-DM DOL starterPart

no.MSC-DM-4-M7(230V50HZ)/MSFAEAN4015081916184Product Length/Depth115 millimetreProduct height180

millimetreProduct width45 millimetreProduct weight0.705 kilogramCertificationsCSA-C22.2 No. 14 (on request)
UL 508 (on request)Product TradenameMSC-DMPProduct TypeDOL starterProduct Sub TypeNoneCatalog NotesIE3-ready
devices are identified by the logo on their packaging.Features & FunctionsFitted with:Short-circuit
releaseFunctionsTemperature compensated overload protectionGeneral informationClassCLASS 10 AConnectionScrew
terminalsConnection to SmartWire-DTNoCoordination type2Degree of protectionIP20
NEMA OtherModelDirect starterMounting methodRail mounting possibleNumber of auxiliary contacts (normally closed
contacts)0Number of auxiliary contacts (normally open contacts)1Overload release current setting - min2.5 AOverload
release current setting - max4 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-DM-4-M7(230V50HZ)/MSFA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.