

INDUSTRIAL COMPONENT DATA

MSC-R-2,5-M7(230V50HZ)-PI 199588 EATON ELECTRIC

Inverter starter 1.6 2.4A Push-in

Brand: EATON - MOELLER | Manufacturer Part Number: MSC-R-2,5-M7(230V50HZ)-PI



Manufacturer	EATON - MOELLER
MPN / Reference	MSC-R-2,5-M7(230V50HZ)-PI
Catalog number	Y7-199588
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-E8428FF523
Generated	2026-08-05

Product Overview

Inverter starter 1.6 - 2.4A; Push-in

Reversing starter, Basic device: MSC, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Motor rating at AC-3, 380 V 400 V 415 V: P= 0.75 kW, Setting range of overload releases: Ir= 1.6 - 2.5 A, Coordination: Type of coordination "1", Type of coordination "2", Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: IEC/EN 60947-4-1, VDE 0676

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

ETIM for 199588 Low-voltage industrial controls and switchgear (EC001037)

Feature Name

Feature Value

Type of motor starter (EF009598)

Reversing starter

With short-circuit release (EF006691)

Yes

Rated control supply voltage AC 50 Hz (EF003978)

230 V

Rated control supply voltage AC 60 Hz (EF003979)

0 V

Rated control supply voltage DC (EF003980)
0 V

Voltage type for actuating (EF008242)
AC

Rated operation power at AC-3, 230 V, 3-phase (EF009599)
0.37 kW

Rated operation power at AC-3, 400 V (EF001364)
0.75 kW

Rated power, 460 V, 60 Hz, 3-phase (EF009600)
0 kW

Rated power, 575 V, 60 Hz, 3-phase (EF009601)
0 kW

Rated operation current I_e (EF001443)
1.9 A

Rated operation current at AC-3, 400 V (EF009602)
2.5 A

Overload release current setting (EF002336)
1.6 A

Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607)
0 A

Rated conditional short-circuit current, type 1, 600 Y/347 V (EF009608)
0 A

Rated conditional short-circuit current, type 2, 230 V (EF009606)
50 A

Rated conditional short-circuit current, type 2, 400 V (EF009605)
50 A

Power consumption (EF000346)
1.4 W

Number of auxiliary contacts as normally open contact (EF001376)
0

Number of auxiliary contacts as normally closed contact (EF001377)
0

Ambient temperature, upper operating limit (EF009603)
55 °C

Temperature compensated overload protection (EF009604)
Yes

Release class (EF006668)
CLASS 10 A

Type of electrical connection of main circuit (EF006819)
Spring clamp connection

Type of electrical connection for a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSC-R-2,5-M7(230V50HZ)-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.