


## INDUSTRIAL COMPONENT DATA

# MSFB-8-125A 191092 Y7-191092 EATON ELECTRIC Board, 8 outgoers, 405mm width, 125 A

Brand: EATON - MOELLER | Manufacturer Part Number: MSFB-8-125A



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | EATON - MOELLER                       |
| MPN / Reference | MSFB-8-125A                           |
| Catalog number  | Y7-191092                             |
| Category        | Busbar system for distribution boards |
| Minimum order   | 1 Pcs                                 |
| Document ID     | EO-3125B3E082                         |
| Generated       | 2026-08-02                            |

## Product Overview

Board, 8 outgoing, 405mm width, 125 A

MSFB-8-125A

Eaton Moeller® series MSF Board, 8 outgoing, 405mm width, 125 A

Board 3 pole, for 8 outgoing, width: 405 mm, rated operating voltage:  $U_e = 690$  V, rated operational current:  $I_e = 125$  A, center-line spacing: 60 mm, mounting position: horizontal, degree of protection: IP20

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

## Additional Product Information

### General specifications

Product Name Eaton Moeller® series MSF Feeder system Catalog Number 191092 Model Code MSFB-8-125A EAN 4015081915903 Product Length/Depth 160 mm Product Height 45 mm Product Width 405 mm Product Weight 1.278 kg

Certifications EN 61439-1 Product specifications

Rated impulse withstand voltage ( $U_{imp}$ ) 6000 V Surface protection Bare Degree of protection IP20 Rated short-time withstand current ( $I_{cw}$ ) 10 kA Mounting position Horizontal Product category Accessories Number of poles Three-pole Busbar distance 60 mm Busbar height 0 mm Busbar thickness - max 0 mm Rated frequency - max 60 Hz Rated frequency - min 50 Hz Rated operational current ( $I_e$ ) - max 125 A Rated operational voltage ( $U_e$ ) - max 690 V Mounting method 60 mm distance between busbar centers Flammability characteristics To UL 94 Material Copper

ETIM for 191092 Power distribution systems (EC001900)

Feature Name

**Feature Value**

Height (EF000040)

45 mm

Width (EF000008)

405 mm

Depth (EF000049)

160 mm

Number of poles (EF001391)

3

Busbar distance (EF002638)

60 mm

Rail height (EF002639)

0 mm

Busbar thickness (EF002640)

0 mm

Rated current (EF000227)

125 A

Short-circuit breaking capacity (I<sub>cw</sub>) (EF002562)

10 kA

Material (EF002169)

Copper

Surface protection (EF000139)

Bare

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / MSFB-8-125A with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.