


INDUSTRIAL COMPONENT DATA

MSFB-8-125A 191092 Y7-191092 EATON ELECTRIC Board, 8 outgoers, 405mm width, 125 A

Brand: EATON - MOELLER | Manufacturer Part Number: MSFB-8-125A



Manufacturer	EATON - MOELLER
MPN / Reference	MSFB-8-125A
Catalog number	Y7-191092
Category	Busbar system for distribution boards
Minimum order	1 Pcs
Document ID	EO-3125B3E082
Generated	2026-08-04

Product Overview

Board, 8 outgoing, 405mm width, 125 A

MSFB-8-125A

Eaton Moeller® series MSF Board, 8 outgoing, 405mm width, 125 A

Board 3 pole, for 8 outgoing, width: 405 mm, rated operating voltage: $U_e = 690$ V, rated operational current: $I_e = 125$ A, center-line spacing: 60 mm, mounting position: horizontal, degree of protection: IP20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series MSF Feeder system Catalog Number 191092 Model Code MSFB-8-125A EAN 4015081915903 Product Length/Depth 160 mm Product Height 45 mm Product Width 405 mm Product Weight 1.278 kg

Certifications EN 61439-1 Product specifications

Rated impulse withstand voltage (U_{imp}) 6000 V Surface protection Bare Degree of protection IP20 Rated short-time withstand current (I_{cw}) 10 kA Mounting position Horizontal Product category Accessories Number of poles Three-pole Busbar distance 60 mm Busbar height 0 mm Busbar thickness - max 0 mm Rated frequency - max 60 Hz Rated frequency - min 50 Hz Rated operational current (I_e) - max 125 A Rated operational voltage (U_e) - max 690 V Mounting method 60 mm distance between busbar centers Flammability characteristics To UL 94 Material Copper

ETIM for 191092 Power distribution systems (EC001900)

Feature Name

Feature Value

Height (EF000040)

45 mm

Width (EF000008)

405 mm

Depth (EF000049)

160 mm

Number of poles (EF001391)

3

Busbar distance (EF002638)

60 mm

Rail height (EF002639)

0 mm

Busbar thickness (EF002640)

0 mm

Rated current (EF000227)

125 A

Short-circuit breaking capacity (I_{cw}) (EF002562)

10 kA

Material (EF002169)

Copper

Surface protection (EF000139)

Bare

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MSFB-8-125A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.