

INDUSTRIAL COMPONENT DATA

T3-6-103/Z 004213 Y7-4213 EATON ELECTRIC Multi-speed switches, Contacts: 11, 32 A, One tapped winding, 2 spe..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-6-103/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-6-103/Z
Catalog number	Y7-4213
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-1F91042B32
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 11, 32 A, One tapped winding, 2 speeds, front plate: 0-Y-D-2, 60 °, maintained, rear mounting

Switch Multi-speed; 11-pole; 32; 1 winding threading; 2 speeds; rating Plate: 0-y-D-2; 60 °; Interlock; Mounting bottom panel Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, rear mounting, 6 contact unit(s), Contacts: 11, 60 °, maintained, With 0 (Off) position, 0-Y-D-2, Design number 103

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 11, Degree of Protection: Front IP65, Design: rear mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 004213 Model Code T3-6-103/Z EAN 4015080042136 Product Length/Depth 179 mm Product Height 54 mm Product Width 61 mm Product Weight 0.366 kg

Certifications CSA File No.: 012528

CSA-C22.2 No. 94

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

UL 60947-4-1

CE

VDE 0660

UL

CSA

IEC/EN 60204

UL Category Control No.: NLRV

IEC/EN 60947-3

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 004213 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No
Housing mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-6-103/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.