

INDUSTRIAL COMPONENT DATA

T3-6-104/Z 004218 Y7-4218 EATON ELECTRIC Multi-speed switches, Contacts: 12, 32 A, One tapped winding, 2 spe..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-6-104/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-6-104/Z
Catalog number	Y7-4218
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-850E8AAF6B
Generated	2026-08-06

Product Overview

Multi-speed switches, Contacts: 12, 32 A, One tapped winding, 2 speeds, front plate: 0-Y-D-2, 60 °, maintained, rear mounting, SOND 29

Switch Multi-speed; 12-pole; 32; 1 winding threading; 2 speeds; rating Plate: 0-y-D-2; 60 °; Interlocking; Installation bottom panel; SOND 29

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, rear mounting, 6 contact unit(s), Contacts: 12, 60 °, maintained, With 0 (Off) position, 0-Y-D-2, SOND 29, Design number 104

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 29, Contacts: 12, Degree of Protection: Front IP65, Design: rear mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 004218 Model Code T3-6-104/Z EAN 4015080042181 Product Length/Depth 179 mm Product Height 54 mm Product Width 61 mm Product Weight 0.366 kg
Certifications CE
CSA Class No.: 3211-05

CSA-C22.2 No. 94

IEC/EN 60947-3

UL 60947-4-1

CSA File No.: 012528

IEC/EN 60947

UL

UL File No.: E36332

CSA

IEC/EN 60204

UL Category Control No.: NLRV

VDE 0660

CSA-C22.2 No. 60947-4-1-14 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 004218 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing mat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-6-104/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.