

INDUSTRIAL COMPONENT DATA

T3-8-137/EZ 005614 Y7-5614 EATON ELECTRIC Multi-speed switches, Contacts: 16, 32 A, 4 speeds, 2 x tapped win..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-8-137/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-8-137/EZ
Catalog number	Y7-5614
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F26E58CE40
Generated	2026-08-06

Product Overview

Multi-speed switches, Contacts: 16, 32 A, 4 speeds, 2 x tapped winding, front plate: 0-1-2-3-4, 60 °, maintained, centre mounting

Switch Multi-speed; 16-pole; 32 A; 4-speed; 2 windings threaded, Plate indicator: 0-1-2-3-4; 60 °; Interlock; recessed Mounting with central fixing

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, centre mounting, 8 contact unit(s), Contacts: 16, 60 °, maintained, With 0 (Off) position, 0-1-2-3-4, Design number 137

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 16, Degree of Protection: Front IP65, Design: center mounting, switching function: 4 speeds, 2 x tapped winding, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2-3-4, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 8 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 005614 Model Code T3-8-137/EZ EAN 4015080056140 Product Length/Depth 182 mm Product Height 54 mm Product Width 61 mm Product Weight 0.412 kg

Certifications CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

CE

VDE 0660

CSA Class No.: 3211-05

IEC/EN 60947-3

UL File No.: E36332

CSA

UL

CSA-C22.2 No. 94

IEC/EN 60204

UL 60947-4-1

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 005614 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-8-137/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.