

INDUSTRIAL COMPONENT DATA

T0-2-35/E 011544 Y7-11544 EATON ELECTRIC Multi-speed switches, Contacts: 4, 20 A, 2 speeds, 2 separate windi..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-35/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-35/E
Catalog number	Y7-11544
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-57C3923300
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 4, 20 A, 2 speeds, 2 separate windings, front plate: 0-1-2, 60 °, maintained, flush mounting, SOND 29

Switch Multi-speed; 4-pole; 20; 2 speeds; 2 separate windings; rating Plate: 0-1-2; 60 °; Interlock; recessed Mounting; SOND 29

Multi-speed switches, T0, 20 A, flush mounting, 2 contact unit(s), Contacts: 4, 60 °, maintained, With 0 (Off) position, 0-1-2, SOND 29, Design number 35

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 29, Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Multi-speed switches, T0, 20 A, flush mounting, 2 contact unit(s), Contacts: 4, 60 °, maintained, With 0 (Off) position, 0-1-2, SOND 29, Design number 35Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 29, Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2

contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton Moeller® series T0 Multi-speed switchPart no.T0-2-35/EEAN4015080115441Product Length/Depth86 millimetreProduct height48 millimetreProduct width48 millimetreProduct weight0.108 kilogramCertificationsCSA-C22.2 No. 94 IEC/EN 60947

CE

CSA

CSA File No.: 012528

UL 60947-4-1

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

UL

UL File No.: E36332

UL Category Control No.: NLRV

IEC/EN 60947-3

VDE 0660

UL

CSAProduct TradenameT0Product TypeMulti-speed switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsEnclosure materialPlasticFitted with:Black thumb grip and front plate

0 (off) positionInscription0-1-2Number of poles2Switch function type2 speeds, 2 sep...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-35/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.