

INDUSTRIAL COMPONENT DATA

T0-2-37/E 011551 Y7-11551 EATON ELECTRIC Multi-speed switches, Contacts: 4, 20 A, 2 speeds, 2 separate windi..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-37/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-37/E
Catalog number	Y7-11551
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-371F276EFD
Generated	2026-08-04

Product Overview

Multi-speed switches, Contacts: 4, 20 A, 2 speeds, 2 separate windings, front plate: 2-0-1, 60 °, maintained, flush mounting
Switch Multi-speed; 4-pole; 20; 2 speeds; 2 separate windings; rating Plate: 2-0-1; 60 °; Interlock; recessed Mounting
Eaton Moeller® series T0 Multi-speed switches, T0, 20 A, flush mounting, 2 contact unit(s), Contacts: 4, 60 °, maintained,
With 0 (Off) position, 2-0-1, Design number 37

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate,
Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 separate windings,
Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 -
60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660,
IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Multi-speed switch Catalog Number 011551 Model Code T0-2-37/E EAN
4015080115519 Product Length/Depth 86 mm Product Height 48 mm Product Width 48 mm Product Weight 0.108 kg

Certifications CSA-C22.2 No. 94

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL

IEC/EN 60947

IEC/EN 60947-3

CSA Class No.: 3211-05

IEC/EN 60204

UL Category Control No.: NLRV

CSA

CSA File No.: 012528

UL File No.: E36332

VDE 0660

CE Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 011551 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Pole switch

Number of poles (EF001391)

2

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-37/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.