

INDUSTRIAL COMPONENT DATA

M22-DRP-G-X 216765 Y7-216765 EATON ELECTRIC

Mushroom actuator, green, without button plate, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DRP-G-X



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DRP-G-X
Catalog number	Y7-216765
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-29C36DB42C
Generated	2026-08-05

Product Overview

Mushroom actuator, green, without button plate, maintained

M22-DRP-G-X

Eaton Moeller® series M22 Mushroom actuator, RMQ-Titan, Mushroom, maintained, Mushroom green, Without button plate, Bezel: titanium

Mushroom actuator, Product range: RMQ-Titan, Single unit, Design: Mushroom, maintained, Color Mushroom: green, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Function: maintained, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Mushroom actuator Catalog Number 216765 Model Code M22-DRP-G-X EAN 4015082167653 Product Length/Depth 37 mm Product Height 43 mm Product Width 37 mm Product Weight 0.016 kg

Compliances CE Marked Certifications IEC 60947-5

CSA Std. C22.2 No. 94-91

EN 60947-5

UL 508

CSA Std. C22.2 No. 14-05

VDE

CSA Class No.: 3211-03

IEC/EN 60947-5

CSA-C22.2 No. 94-91

UL Category Control No.: NKCR

VDE 0660

CSA

CSA File No.: 012528

IEC/EN 60947

UL

CSA-C22.2 No. 14-05

CE

UL File No.: E29184

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Color Green Design Mushroom-shaped

Classical Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device General

Degree of protection NEMA 12

IP67

IP69K

NEMA 13

NEMA 3R

IP66

NEMA 4X Degree of protection (front side) IP67/IP69K

NEMA 4X Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 22.5 mm Operating frequency 1800

Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Mushroom-headed pushbutton

Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min

40 °C Ambient storage temperature - max 80 °C Climatic proofin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DRP-G-X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.