

INDUSTRIAL COMPONENT DATA

M22S-DP-R-X0 216721 Y7-216721 EATON ELECTRIC

Mushroom actuator, red 0, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DP-R-X0



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DP-R-X0
Catalog number	Y7-216721
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-32C2C226E1
Generated	2026-08-04

Product Overview

Mushroom actuator, red 0, momentary

M22S-DP-R-X0

Eaton Moeller® series M22 Mushroom actuator, RMQ-Titan, Mushroom, momentary, Mushroom red, red, inscribed, Bezel: black

Mushroom actuator, Product range: RMQ-Titan, Single unit, Design: Mushroom, momentary, Color Mushroom: red, button plate: red, inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Function: momentary, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Mushroom actuator Catalog Number 216721 Model Code M22S-DP-R-X0 EAN 4015082167219 Product Length/Depth 37 mm Product Height 43 mm Product Width 37 mm Product Weight 0.016 kg

Certifications CE

IEC/EN 60947-5

VDE 0660

CSA Class No.: 3211-03

IEC/EN 60947

UL File No.: E29184

UL
CSA-C22.2 No. 94-91
UL 508
UL Category Control No.: NKCR
CSA
CSA File No.: 012528
CSA-C22.2 No. 14-05
DNV
GL
LR Features & Functions
Bezel color Black Bezel material Plastic Design Mushroom-shaped
Classical Fitted with: Front ring Inscription Inscribed Unlocking method None General
Degree of protection IP67/IP69K
NEMA 4X, 13 Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600
Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Mushroom-headed pushbutton
Ambient conditions, mechanical
Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27
30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min
40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Communication
Connection to SmartWire-DT With SWD-RMQ connections
Yes Actuator
Actuating force 5 N Actuator color Red Actuator function Momentary
Spri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DP-R-X0 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.