

## INDUSTRIAL COMPONENT DATA

# M22S-DRP-W-X1 216758 Y7-216758 EATON ELECTRIC

## Mushroom actuator, white I, maintained

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DRP-W-X1



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | EATON - MOELLER               |
| MPN / Reference | M22S-DRP-W-X1                 |
| Catalog number  | Y7-216758                     |
| Category        | Front element for push button |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-F76CBFAEE3                 |
| Generated       | 2026-08-04                    |

### Product Overview

Mushroom actuator, white I, maintained

M22S-DRP-W-X1

Eaton Moeller® series M22 Mushroom actuator, RMQ-Titan, Mushroom, maintained, Mushroom black, White, inscribed, Bezel: black

Mushroom actuator, Product range: RMQ-Titan, Single unit, Design: Mushroom, maintained, Color Mushroom: black, button plate: White, Button plate inscribed, Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Function: maintained, Instructions: Stay-put/spring-return function can be changed on device, Standards: IEC/EN 60947, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Mushroom actuator Catalog Number 216758 Model Code M22S-DRP-W-X1

EAN 4015082167585 Product Length/Depth 37 mm Product Height 43 mm Product Width 37 mm Product Weight 0.016 kg

Certifications CSA

VDE 0660

CE

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

UL Category Control No.: NKCR

IEC/EN 60947

UL 508

UL File No.: E29184

IEC/EN 60947-5

UL

CSA Class No.: 3211-03

CSA File No.: 012528

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design Mushroom-shaped

Classical Features Labelled Fitted with: Front ring Functions Stay-put/spring-return function can be changed on device

Inscription Inscribed General

Degree of protection NEMA 3R

NEMA 4X

IP69K

NEMA 12

NEMA 13

IP66

IP67 Degree of protection (front side) IP67/IP69K

NEMA 4X Lifespan, mechanical 1,000,000 Operations (AC operated) Opening diameter 22.5 mm Operating frequency 1800

Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Mushroom-headed pushbutton

Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min

-40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 6006...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DRP-W-X1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.