

INDUSTRIAL COMPONENT DATA

M22-DP-Y 216718 Y7-216718 EATON ELECTRIC Mushroom actuator, yellow, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22-DP-Y



Manufacturer	EATON - MOELLER
MPN / Reference	M22-DP-Y
Catalog number	Y7-216718
Category	Front element for mushroom push-button
Minimum order	5 Pcs
Document ID	EO-1B29E01AF2
Generated	2026-08-04

Product Overview

Mushroom actuator, yellow, momentary

M22-DP-Y

Mushroom actuator, RMQ-Titan, Mushroom, momentary, Mushroom yellow, yellow, Blank, Bezel: titanium

Mushroom actuator, Product range: RMQ-Titan, Single unit, Design: Mushroom, momentary, Color Mushroom: yellow, button plate: yellow, Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Function: momentary, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Mushroom actuator Catalog Number 216718 Model Code M22-DP-Y EAN 4015082167189 Product Length/Depth 37 mm Product Height 43 mm Product Width 37 mm Product Weight 0.016 kg

Compliances CE Marked Certifications IEC 60947-5

EN 60947-5

UL 508

CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-05

VDE

CSA-C22.2 No. 94-91

IEC/EN 60947-5

VDE 0660

CSA Class No.: 3211-03

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

CE

UL

IEC/EN 60947

CSA

CSA File No.: 012528

UL File No.: E29184

DNV

GL

LR Features & Functions

Bezel color Titanium Bezel material Plastic Design Mushroom-shaped

Classical Fitted with: Front ring Inscription Blank Unlocking method None General

Degree of protection IP67/IP69K

NEMA 4X, 13 Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600

Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Mushroom-headed pushbutton

Ambient conditions, mechanical

Mounting position As required Shock resistance Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min

40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Communication

Connection to SmartWire-DT With SWD-RMQ co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22-DP-Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.