

INDUSTRIAL COMPONENT DATA

M22S-DP-Y 216719 Y7-216719 EATON ELECTRIC Mushroom actuator, yellow, momentary

Brand: EATON - MOELLER | Manufacturer Part Number: M22S-DP-Y



Manufacturer	EATON - MOELLER
MPN / Reference	M22S-DP-Y
Catalog number	Y7-216719
Category	Front element for mushroom push-button
Minimum order	1 Pcs
Document ID	EO-B4EDB6E883
Generated	2026-08-05

Product Overview

Mushroom actuator, yellow, momentary

M22S-DP-Y

Eaton Moeller® series M22 Mushroom actuator, RMQ-Titan, Mushroom, momentary, Mushroom yellow, yellow, Blank, Bezel: black

Mushroom actuator, Product range: RMQ-Titan, Single unit, Design: Mushroom, momentary, Color Mushroom: yellow, button plate: yellow, Blank, Degree of Protection: IP66, IP67, IP69K, Bezel: black, Connection to SmartWire-DT: yes, with SWD-RMQ connections, Front dimensions: 22 x 22, Function: momentary, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series M22 Mushroom actuator Catalog Number 216719 Model Code M22S-DP-Y EAN 4015082167196 Product Length/Depth 37 mm Product Height 43 mm Product Width 37 mm Product Weight 0.016 kg

Certifications VDE 0660

CSA-C22.2 No. 94-91

CSA-C22.2 No. 14-05

UL 508

IEC/EN 60947-5

UL

UL File No.: E29184

CSA File No.: 012528

IEC/EN 60947

CSA

UL Category Control No.: NKCR

CE

CSA Class No.: 3211-03

DNV

GL

LR Features & Functions

Bezel color Black Bezel material Plastic Design Mushroom-shaped

Classical Fitted with: Front ring Illumination Non-illuminated Inscription Blank Unlocking method None General

Degree of protection IP67/IP69K

NEMA 4X, 13 Lifespan, mechanical 5,000,000 Operations Opening diameter 22.5 mm Operating frequency 3600

Operations/h Product category RMQ-Titan Size Front dimensions: 22 x 22 mm Type Mushroom-headed pushbutton

Ambient conditions, mechanical

Mounting position As required Shock resistance 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Mechanical, According to IEC/EN 60068-2-27 Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min 40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Communication

Connection to SmartWire-DT With SWD-RMQ connections

Yes Actuator

Actuating force 5 N Actuator color Yellow Actuator...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / M22S-DP-Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.