

INDUSTRIAL COMPONENT DATA

MVS-SB-EM 220213 Y7-220213 EATON ELECTRIC Secondary terminal wire kit, star-delta, for DILEM

Brand: EATON - MOELLER | Manufacturer Part Number: MVS-SB-EM



Manufacturer	EATON - MOELLER
MPN / Reference	MVS-SB-EM
Catalog number	Y7-220213
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-468B5B7FF5
Generated	2026-08-05

Product Overview

Secondary terminal wire kit, star-delta, for DILEM

MVS-SB-EM

Eaton Moeller® series MVS Secondary terminal wire kit, star-delta, for DILEM

Star-delta wiring kit for frame sizes DILEE-DILE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series MVS Accessory Wiring kit Catalog Number 220213 Model Code MVS-SB-EM EAN 4015082202132 Product Length/Depth 84 mm Product Height 28 mm Product Width 21 mm Product Weight 0.029 kg

Certifications CSA-C22.2 No. 14-05

IEC/EN 60947-4-1

CSA Class No.: 3211-06

CSA

UL

CSA File No.: 012528

UL File No.: E36332

CE

UL 508

UL Category Control No.: NLRV7 Catalog Notes The following control cables are integrated in addition to electrical interlock: Features & Functions

Fitted with: Control cables: Q13: A1 - Q15: 21

Control cables: Q13: 21 - Q15: A1

Control cables: Q13: A2 - Q15: A2 Functions For star-delta combination incl. star-point bridge General

Accessory/spare part type Connecting bridge Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 2.1 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0.7 W Rated operational current for specified heat dissipation (I_n) 22 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MVS-SB-EM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.