

INDUSTRIAL COMPONENT DATA

N2-4-250-S15-DC 167690 Y7-167690 EATON ELECTRIC Switch disconnecter N, 4P 250A, 1500VDC

Brand: EATON - MOELLER | Manufacturer Part Number: N2-4-250-S15-DC



Manufacturer	EATON - MOELLER
MPN / Reference	N2-4-250-S15-DC
Catalog number	Y7-167690
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-CC30AD6B00
Generated	2026-08-06

Product Overview

Switch disconnecter N, 4P 250A, 1500VDC

N2-4-250-S15-DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 4p 250A 1500VDC

Switch-disconnectors N..DC in the special version for up to 1500 V DC can be used on 1- or 2 poles. They comply with the isolation properties even for earthed IT networks. Accessories, such as bridge kits, connection terminals and door coupling rotary handles enable individual installation in the most varied of distribution systems. Auxiliary switches, voltage releases and remote operators facilitate signaling and automation. Notes: main switch characteristics including positive drive according to IEC/EN 60204 und VDE 0113. Isolating characteristics according to IEC/EN 60947-3 and VDE 0660. Terminal type: a series connection is required for 2 pole switching according to the specified connecting possibilities. See accessories bridge kits. Switch can not be combined with plug-in / withdrawable units and / or connection on rear. for non-earthed networks > 1000VDC the installation must be configured such that the likelihood of a double earth fault is negligibly small.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM switch-disconnector Catalog Number 167690 Model Code N2-4-250-S15-DC EAN 4015081642335 Product Length/Depth 149 mm Product Height 184 mm Product Width 140 mm Product Weight 3.5 kg
Compliances RoHS conform Certifications IEC Product specifications

Type DC switch-disconnector Special features Application Open areas

Utility buildings

Amperage Rating 250 A Voltage rating 1500 V - 1500 V Circuit breaker frame type N2 Features Version as emergency stop installation

Motor drive optional

Version as main switch

Version as maintenance-/service switch

Remote operation with shunt releases / remote operator 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Re...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / N2-4-250-S15-DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.