

INDUSTRIAL COMPONENT DATA

N4-4-1000-S15-DC 166414 Y7-166414 EATON ELECTRIC

Switch disconnecter N, 4P, 1000A, 1500VDC

Brand: EATON - MOELLER | Manufacturer Part Number: N4-4-1000-S15-DC



Manufacturer	EATON - MOELLER
MPN / Reference	N4-4-1000-S15-DC
Catalog number	Y7-166414
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-E4A8719B04
Generated	2026-08-04

Product Overview

Switch disconnecter N, 4P, 1000A, 1500VDC

N4-4-1000-S15-DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 4p 1000A 1500VDC

Switch-disconnectors N..DC in the special version for up to 1500 V DC can be used on 1- or 2 poles. They comply with the isolation properties even for earthed IT networks. Accessories, such as bridge kits, connection terminals and door coupling rotary handles enable individual installation in the most varied of distribution systems. Auxiliary switches, voltage releases and remote operators facilitate signaling and automation. Notes: main switch characteristics including positive drive according to IEC/EN 60204 und VDE 0113. Isolating characteristics according to IEC/EN 60947-3 and VDE 0660 . Terminal type: a series connection is required for 2 pole switching according to the specified connecting possibilities. See accessories bridge kits. Switch can not be combined with plug-in / withdrawable units and / or connection on rear. for non-earthed networks > 1000VDC the installation must be configured such that the likelihood of a double earth fault is negligibly small.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM switch-disconnector Catalog Number 166414 Model Code N4-4-1000-S15-DC
EAN 4015081629220 Product Length/Depth 401 mm Product Height 207 mm Product Width 280 mm Product Weight
22.656 kg Compliances RoHS conform Certifications IEC Product specifications

Type DC switch-disconnector Switch-disconnector Special features IEC/EN 60947-3 CCC China Compulsory Certificate Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113. Isolating characteristics to IEC/EN 60947-3 and VDE 0660. N switch-disconnectors can, in addition, be combined with NZM...-XU, NZM...-XA shunt releases and auxiliary contacts as well as with NZM...-XR... remote operator. For DC switching, all 4 contacts must be connected in series. Refer to the information on jumper kit accessories. Supplied as standard: Screw connection box terminal optional. When working with ungrounded systems (e.g., IT), the installation must ensure that a double ground fault will be impossible. Switch can not be combined with plug-in/withdrawable units and/or connection on rear. Lifespan, mechanical: of which max. 50 % trip by shunt/undervoltage release Rated current = rated uninterrupted current: 1000 A Values for rated uninterrupted current at 65 °C include jumpers. Application Open areas Utility buildings Amperage Rating 1000 A Voltage rating 1500 V - 1500 V Circuit breaker frame type N4 Features Version as maintenance-/service switch Version as main switch Remote o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / N4-4-1000-S15-DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.