

INDUSTRIAL COMPONENT DATA

N4-4-1400-S15-DC 166416 Y7-166416 EATON ELECTRIC

Switch disconnecter N, 4P 1400A, 1500VDC

Brand: EATON - MOELLER | Manufacturer Part Number: N4-4-1400-S15-DC



Manufacturer	EATON - MOELLER
MPN / Reference	N4-4-1400-S15-DC
Catalog number	Y7-166416
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-1BD3B8E738
Generated	2026-08-05

Product Overview

Switch disconnecter N, 4P 1400A, 1500VDC

N4-4-1400-S15-DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 4p 1400A 1500VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM switch-disconnector Catalog Number 166416 Model Code N4-4-1400-S15-DC
EAN 4015081629244 Product Length/Depth 401 mm Product Height 207 mm Product Width 280 mm Product Weight 22 kg
Compliances RoHS conform Certifications IEC Product specifications

Type DC switch-disconnector Switch-disconnector Special features IEC/EN 60947-3CCC China Compulsory CertificateMain switch characteristics including positive drive to IEC/EN 60204 and VDE 0113.Isolating characteristics to IEC/EN 60947-3 and VDE 0660.N switch-disconnectors can, in addition, be combined with NZM...-XU, NZM...-XA shunt releases and auxiliary contacts as well as with NZM...-XR... remote operator.For DC switching, all 4 contacts must be connected in series. Refer to the information on jumper kit accessories.Supplied as standard: Screw connectionbox terminal optional.When working with ungrounded systems (e.g., IT), the installation must ensure that a double ground fault will be impossible.Switch can not be combined with plug-in/withdrawable units and/or connection on rear.Lifespan, mechanical: of which max. 50 % trip by shunt/undervoltage releaseRated current = rated uninterrupted current: 1400 AValues for rated uninterrupted current at 65 °C include jumpers. Application Open areasUtility buildings Amperage Rating 1400 A Voltage

rating 1500 V - 1500 V Circuit breaker frame type N4 Features Version as main switch

Version as maintenance-/service switch

Version as e...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / N4-4-1400-S15-DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.