

INDUSTRIAL COMPONENT DATA

N4-4-800-S15-DC 166413 Y7-166413 EATON ELECTRIC Switch disconnecter N, 4P 800A, 1500VDC

Brand: EATON - MOELLER | Manufacturer Part Number: N4-4-800-S15-DC



Manufacturer	EATON - MOELLER
MPN / Reference	N4-4-800-S15-DC
Catalog number	Y7-166413
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-79539526D1
Generated	2026-08-04

Product Overview

Switch disconnecter N, 4P 800A, 1500VDC

N4-4-800-S15-DC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 4p 800A 1500VDC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers NZM**

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM switch-disconnector Catalog Number 166413 Model Code N4-4-800-S15-DC EAN 4015081629213 Product Length/Depth 401 mm Product Height 207 mm Product Width 280 mm Product Weight 22.723 kg

Compliances RoHS conform Certifications IEC Product specifications

Type DC switch-disconnector Switch-disconnector Special features IEC/EN 60947-3CCC China Compulsory Certificate Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113. Isolating characteristics to IEC/EN 60947-3 and VDE 0660. N switch-disconnectors can, in addition, be combined with NZM...-XU, NZM...-XA shunt releases and auxiliary contacts as well as with NZM...-XR... remote operator. For DC switching, all 4 contacts must be connected in series. Refer to the information on jumper kit accessories. Supplied as standard: Screw connection box terminal optional. When working with ungrounded systems (e.g., IT), the installation must ensure that a double ground fault will be impossible. Switch can not be combined with plug-in/withdrawable units and/or connection on rear. Lifespan, mechanical: of which max. 50 % trip by shunt/undervoltage release Rated current = rated uninterrupted current: 800 A Values for rated uninterrupted current at 65 °C include jumpers. Application Open areas Utility buildings Amperage Rating 800 A Voltage

rating 1500 V - 1500 V Circuit breaker frame type N4 Features Remote operation with shunt releases / remote operator
Motor drive option...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / N4-4-800-S15-DC with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.