

INDUSTRIAL COMPONENT DATA

N-P1Z 000652 Y7-652 EATON ELECTRIC Neutral conductor, 4th pole, N for P1Z

Brand: EATON - MOELLER | Manufacturer Part Number: N-P1Z



Manufacturer	EATON - MOELLER
MPN / Reference	N-P1Z
Catalog number	Y7-652
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-A666E71528
Generated	2026-08-04

Product Overview

Neutral conductor, 4th pole, N for P1Z

Module for Neutral conductor; 4th poles; For P1-.../Z

Eaton Moeller® series Neutral conductor, 4th pole, N for P1Z

Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, center mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series Accessory Neutral conductor Catalog Number 000652 Model Code N-P1Z EAN 4015080006527 Product Length/Depth 32 mm Product Height 70 mm Product Width 15 mm Product Weight 0.03 kg

Certifications CSA-C22.2 No. 14-05

UL Category Control No.: NLRV

CSA-C22.2 No. 94

CSA

UL File No.: E36332

CE

UL 508

CSA File No.: 012528

IEC/EN 60947-3

UL

CSA Class No.: 3211-05 General

Accessory/spare part type Neutral terminal Mounting position Left side

Right side Type Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Terminal capacities

Stripping length (main cable) 10.5 mm Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 1.8 W Rated operational current for specified heat dissipation (I_n) 32 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal

heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements. 10.2.5 Lifting Does n...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / N-P1Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.