

INDUSTRIAL COMPONENT DATA

N-P3Z 064805 Y7-64805 EATON ELECTRIC Neutral conductor, switched neutral

Brand: EATON - MOELLER | Manufacturer Part Number: N-P3Z



Manufacturer	EATON - MOELLER
MPN / Reference	N-P3Z
Catalog number	Y7-64805
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-E683A14F02
Generated	2026-08-05

Product Overview

Neutral conductor, switched neutral

Module for Neutral 4th Pole Conductor for P3-.../Z

Eaton Moeller® series Neutral conductor, switched neutral

Accessories to cam switches T/switch-disconnectors P according to IEC/EN60947-3, design general: insulating material-surface mounting enclosure , flush mounting, center mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series Accessory Neutral conductor Catalog Number 064805 Model Code N-P3Z EAN 4015080648055 Product Length/Depth 40.5 mm Product Height 82.2 mm Product Width 18 mm Product Weight 0.07 kg

Certifications CSA File No.: 012528

UL

CSA-C22.2 No. 14-05

CSA Class No.: 3211-05

IEC/EN 60947-3

CE

CSA

UL 508

UL Category Control No.: NLRV

CSA-C22.2 No. 94

UL File No.: E36332 General

Accessory/spare part type Neutral terminal Mounting position Right side

Left side Type Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Terminal capacities

Stripping length (main cable) 13.5 mm Electrical rating

Rated operational current (Ie) - max 90 A Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 7.5 W Rated operational current for specified heat dissipation (I_n) 100 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal

heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV)

radiation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / N-P3Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.