

INDUSTRIAL COMPONENT DATA

NEXILITE 250lm 1h IP65 NXL250-IP EATON ELECTRIC

NEXILITE 250lm 1H IP65

Brand: EATON - MOELLER | Manufacturer Part Number: NEXILITE 250lm 1h IP65



Manufacturer	EATON - MOELLER
MPN / Reference	NEXILITE 250lm 1h IP65
Catalog number	NXL250IP
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-205C21CC90
Generated	2026-08-06

Product Overview

NEXILITE 250lm 1H IP65

Eaton NexiLite, Safety lighting/ exit sign, 20m viewing distance, Escape route, Stand alone, LED, Non-Maintained operation, IP65, 250lm, 1 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Self contained
--------------	----------------------------------

Additional Product Information

ETIM for NXL250-IP Luminaires (EC001957)

Feature Name

Feature Value

Mounting method (EF000003)

Surface mounting/recessed mounting

Suitable for labelling type (EF001277)

Insert sheet/plate

With pictogram (EF011099)

No

Monitoring equipment (EF008091)

None

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)
Peripheral (individual battery)
Battery technology (EF004351)
NiCd
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
1
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
24
Housing material (EF001596)
Plastic
Housing colour (EF000136)
White
Material cover (EF004284)
Plastic transparent
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
230 V
Type of control gear (EF000381)
LED driver constant current
Light distributor (EF012170)
Reflector
Degree of protection (IP) (EF005474)
IP65
Impact strength (EF004293)
IK07
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
1.4 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
250 lm
Colour temperature (EF009346)
5700 K
Power factor (EF025740)
0.442
Recognition distance (EF008732)

20 m

Nominal operation time (EF012518)

1 h

Width (EF000008)

125 mm

Height/depth (EF001456)

53 mm

Length (EF001438)

308 mm

Built-in width (EF000846)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NEXILITE 250lm 1h IP65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.