

INDUSTRIAL COMPONENT DATA

NEXITECH LED 150lm 1H IP65 AT NEXI150-AT-IP EATON

ELECTRIC NEXITECH LED 150lm 1H IP65 AT

Brand: EATON - MOELLER | Manufacturer Part Number: NEXITECH LED 150lm 1H IP65 AT



Manufacturer	EATON - MOELLER
MPN / Reference	NEXITECH LED 150lm 1H IP65 AT
Catalog number	NEXI150-AT-IP
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-C1E572847F
Generated	2026-08-05

Product Overview

NEXITECH LED 150lm 1H IP65 AT

Eaton NexiTech LED, Safety lighting/ exit sign, 20m viewing distance, Escape route, Auto-Test, LED, Maintained / Non-Maintained operation, IP65, 150lm, 1 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Self Contained -Safe Lite

Additional Product Information

General specifications

Product Name Eaton NexiTech LED SC Emergency Luminaire Catalog Number NEXI150-AT-IP EAN 3660191603083

Product Length/Depth 308 mm Product Height 53 mm Product Width 125 mm Product Weight 0.631 kg Certifications Not Applicable Product specifications

Battery quality NiCd Permissible ambient temperature - min 5 °C Permissible ambient temperature - max 30 °C Protection class II Degree of impact resistance (IK) IK 07 Outdoor use compliance False Explosion protected False Diameter 9999 in Degree of protection IP65 Mode Maintained / Non-Maintained (M / NM) Lamp type LED not exchangeable With light source True Lamp holder None Lamp power 1.5 W Type of indicator Not applicable Monitoring equipment Automatic self test Power supply system Peripheral (individual battery) Circuit Other Voltage type AC Nominal current - max 10.9 mA Nominal current - min 2.7 mA Power factor .52 Wiring system Continuous circuit/emergency circuit With remote switch connection True Conductor cross section 2.5 Connection type Plug-in connection Max. system power 2.4 W Rated life time L80/B10 at 25 °C 70000 hour Type of control gear LED operating device current-controlled Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Rated ambient temp acc. IEC62722-2-1 - Min 5 °C Rated ambient temp acc. IEC62722-2-1 - Max

30 °C Nominal operation time - min 1 hour Nominal operation time - max 1 hour Autonomy 1 hour Mounting Method Surface mounting/recessed mounting Material housing Plastic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NEXITECH LED 150lm 1H IP65 AT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.