

INDUSTRIAL COMPONENT DATA

NEXITECH LED 150LM 3H CGLine+ NEXI150-3H-CGL EATON ELECTRIC NEXITECH LED 150LM 3H CGLINE+

Brand: EATON - MOELLER | Manufacturer Part Number: NEXITECH LED 150LM 3H CGLine+



Manufacturer	EATON - MOELLER
MPN / Reference	NEXITECH LED 150LM 3H CGLine+
Catalog number	NEXI150-3H-CGL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-CA2DCF7C86
Generated	2026-08-05

Product Overview

NEXITECH LED 150LM 3H CGLINE+

NEXITECH LED 150LM 3H CGLine+

Eaton NexiTech LED, Safety lighting/ exit sign, 20m viewing distance, Escape route, CGLine + technology, LED, Maintained / Non-Maintained operation, IP40, 150lm, 3 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Central Battery System
--------------	--

Additional Product Information

General specifications

Product Name Eaton NexiTech LED SC Emergency Luminaire Catalog Number NEXI150-3H-CGL EAN 3660191602482

Product Length/Depth 290 mm Product Height 40 mm Product Width 110 mm Product Weight 0.64 kg Certifications CE

Applications

Mounting Method Surface mounting/recessed mounting Outdoor use compliance False Type of indicator Not applicable

Electrical specs

Battery quality NiCd Circuit Other Connection type Plug-in connection Explosion protected False Power supply system

Peripheral (individual battery) Protection class II Type of control gear LED operating device current-controlled Voltage type

AC Wiring system Continuous circuit/emergency circuit General specs

Function Escape route lighting/signage Kind of luminaire Safety and exit sign luminaire Labelling type Insert sheet/plate

Light distributor Reflector Mode Maintained / Non-Maintained (M / NM) Pictogram included False With remote switch

connection True Housing specs

Color housing White Degree of protection IP40 Impact strength IK03 Material cover Plastic, transparent Material housing Plastic Light source specs
Color of light White Color rendering index (CRI) 70-79 Degree of impact resistance (IK) IK 03 Energy efficiency class of the built-in lamp A++, A+, A (LED) Lamp holder None Lamp type LED not exchangeable With light source True Monitoring options
Monitoring equipment Safety module for monitoring (central feeded system) Testing systems
Testing system CGLine +
ETIM for NEXI150-3H-CGL Luminaires (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NEXITECH LED 150LM 3H CGLine+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.