

INDUSTRIAL COMPONENT DATA

NEXITECH LED 1h IA CGLine+ IP65 NEXI1HIACGLIP EATON

ELECTRIC NEXITECH LED 1h IA CGLine+ IP65

Brand: EATON - MOELLER | Manufacturer Part Number: NEXITECH LED 1h IA CGLine+ IP65



Manufacturer	EATON - MOELLER
MPN / Reference	NEXITECH LED 1h IA CGLine+ IP65
Catalog number	NEXI1HIACGLIP
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-1865F5D668
Generated	2026-08-06

Product Overview

NEXITECH LED 1h IA CGLine+ IP65

Eaton NexiTech LED, Exit sign with Increased Affordance, 20m viewing distance, Escape route, CGLine + technology, LED, Maintained / Non-Maintained operation, IP65, 80lm, 1 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Central Battery System
--------------	--

Additional Product Information

General specifications

Product Name Eaton NexiTech LED SC Emergency Luminaire Catalog Number NEXI1HIACGLIP EAN 3660191609269

Product Length/Depth 308 mm Product Height 53 mm Product Width 125 mm Product Weight 0.766 kg Certifications CE

Product specifications

Battery quality NiCd Protection class II Degree of protection IP65 Lamp type LED not exchangeable With light source True Lamp holder None Type of indicator Only single-sided Monitoring equipment Safety module for monitoring (central feeded system) Power supply system Peripheral (individual battery) Voltage type AC Power factor .41 Wiring system Continuous circuit/emergency circuit With remote switch connection True Conductor cross section 2.5 Connection type Plug-in connection Max. system power 3.9 W Rated life time L80/B10 at 25 °C 70000 hour Type of control gear LED operating device current-controlled Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Rated ambient temp acc. IEC62722-2-1 - Min 5 °C Rated ambient temp acc. IEC62722-2-1 - Max 30 °C Nominal operation time - min 1 hour Nominal operation time - max 1 hour Mounting Method Surface mounting/recessed mounting Material housing Plastic Color housing White Material cover Plastic, transparent Labelling type Insert sheet/plate Pictogram included True Built-in Length 272 mm

Built-in Width 95 mm Built-in height/depth 96 mm Number Of Poles (Numeric) 2 Impact strength IK07 Rated Luminous Flux
Acc. IEC 62722-2-1 80 lm Color temperature - max 5053 K Color temp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NEXITECH LED 1h IA CGLine+ IP65 with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.