

INDUSTRIAL COMPONENT DATA

NEXITECH LED 250 1H30 AT NEXI250-AT EATON ELECTRIC
NEXITECH LED 250 1H30 AT

Brand: EATON - MOELLER | Manufacturer Part Number: NEXITECH LED 250 1H30 AT



Manufacturer	EATON - MOELLER
MPN / Reference	NEXITECH LED 250 1H30 AT
Catalog number	NEXI250-AT
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-9A280CD560
Generated	2026-08-05

Product Overview

NEXITECH LED 250 1H30 AT

Eaton NexiTech LED, Safety lighting/ exit sign, 20m viewing distance, Escape route, Auto-Test, LED, Maintained / Non-Maintained operation, IP40, 250lm, 1.5 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Self Contained -Safe Lite
--------------	---

Additional Product Information

General specifications

Product Name Eaton NexiTech LED SC Emergency Luminaire Catalog Number NEXI250-AT EAN 3660191600198 Product Length/Depth 290 mm Product Height 40 mm Product Width 110 mm Product Weight 1.45 kg Certifications Not Applicable

Product specifications

Battery quality NiCd Permissible ambient temperature - min 5 °C Permissible ambient temperature - max 30 °C Protection class II Degree of impact resistance (IK) IK 03 Outdoor use compliance False Explosion protected False Diameter 9999 in Degree of protection IP40 Mode Maintained / Non-Maintained (M / NM) Lamp type LED not exchangeable With light source True Lamp holder None Lamp power 4.5 W Type of indicator Not applicable Monitoring equipment Automatic self test Power supply system Peripheral (individual battery) Circuit Other Voltage type AC Nominal current - max 10.2 mA Nominal current - min 9.4 mA Power factor .55 Wiring system Continuous circuit/emergency circuit With remote switch connection True Conductor cross section 2.5 Connection type Plug-in connection Max. system power 3.6 W Rated life time L80/B10 at 25 °C 70000 hour Type of control gear LED operating device current-controlled Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Rated ambient temp acc. IEC62722-2-1 - Min 5 °C Rated ambient temp acc. IEC62722-2-1 - Max

30 °C Nominal operation time - min 1.5 hour Nominal operation time - max 1.5 hour Autonomy 1.5 hours Mounting Method
Surface mounting/recessed mounting Material housing Plas...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NEXITECH LED 250 1H30 AT with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.