

INDUSTRIAL COMPONENT DATA

NEXITECH LED 300LM 3H CGLine+ NEXI300-3H-CGL EATON ELECTRIC NEXITECH LED 300LM 3H CGLINE+

Brand: EATON - MOELLER | Manufacturer Part Number: NEXITECH LED 300LM 3H CGLine+



Manufacturer	EATON - MOELLER
MPN / Reference	NEXITECH LED 300LM 3H CGLine+
Catalog number	NEXI300-3H-CGL
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-F55ADC8948
Generated	2026-08-06

Product Overview

NEXITECH LED 300LM 3H CGLINE+

NEXITECH LED 300LM 3H CGLine+

Eaton NexiTech LED, Safety lighting/ exit sign, 20m viewing distance, Escape route, CGLine + technology, LED, Maintained / Non-Maintained operation, IP40, 300lm, 3 hour duration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Central Battery System
--------------	--

Additional Product Information

General specifications

Product Name Eaton NexiTech LED SC Emergency Luminaire Catalog Number NEXI300-3H-CGL EAN 3660191602444

Product Length/Depth 290 mm Product Height 40 mm Product Width 110 mm Product Weight 0.64 kg Certifications Not Applicable Product specifications

Battery voltage 7.2 V Battery quality NiCd Permissible ambient temperature - min 5 °C Permissible ambient temperature -

max 30 °C Protection class II Degree of impact resistance (IK) IK 03 Outdoor use compliance False Explosion protected

False Diameter 9999 in Degree of protection IP40 Mode Maintained / Non-Maintained (M / NM) Lamp type LED not

exchangeable With light source True Lamp holder None Lamp power 4.5 W Type of indicator Not applicable Monitoring

equipment Safety module for monitoring (central feeded system) Power supply system Peripheral (individual battery) Circuit

Other Voltage type AC Nominal current - max 16.3 mA Nominal current - min 9.4 mA Power factor .55 Wiring system

Continuous circuit/emergency circuit With remote switch connection True Conductor cross section 2.5 Connection type

Plug-in connection Max. system power 3.6 W Rated life time L80/B10 at 25 °C 70000 hour Type of control gear LED

operating device current-controlled Nominal voltage AC - max 240 V Nominal voltage AC - min 220 V Rated ambient temp
acc. IEC62722-2-1 - Min 5 °C Rated ambient temp acc. IEC62722-2-1 - Max 30 °C Nominal operation time - min 3 hour
Nominal operation time - max 3 hour Autonomy 3 hours Mounting Method Sur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NEXITECH LED 300LM 3H CGLine+ with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.