

## INDUSTRIAL COMPONENT DATA

**NH FUSE 10A 500V GG/GL SIZE 01 10NHG01BI 0001664035**  
**EATON ELECTRIC Fuse-link, LV, 10 A, AC 500 V, NH01, gL/g..**

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 10A 500V GG/GL SIZE 01



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | EATON - MOELLER                |
| MPN / Reference | NH FUSE 10A 500V GG/GL SIZE 01 |
| Catalog number  | 0001664035                     |
| Category        | Low Voltage HRC fuse           |
| Minimum order   | 3 Pcs                          |
| Document ID     | EO-73580A4243                  |
| Generated       | 2026-08-06                     |

**Product Overview**

Fuse-link, LV, 10 A, AC 500 V, NH01, gL/gG, IEC, dual indicator, live gripping lugs

NH FUSE 10A 500V GG/GL SIZE 01

Fuse-link, low voltage, 10 A, AC 500 V, 120 kA, NH01, gL/gG, IEC, dual indicator, insulated gripping lugs

Fuse, Fuse-link, low voltage, 10 A, AC 500 V, NH01, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

**Additional Product Information**

Fuse-link, low voltage, 10 A, AC 500 V, 120 kA, NH01, gL/gG, IEC, dual indicator, insulated gripping lugs  
Fuse, Fuse-link, low voltage, 10 A, AC 500 V, NH01, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA  
Delivery program

Product range Fuse  
Basic function Fuse-link  
Field of application low voltage  
Rated current [I]<sub>n</sub> 10 A  
Rated voltage AC 500 V  
Construction size NH01  
Utilization category gL/gG  
Status indicator dual indicator  
Description insulated gripping lugs  
Breaking Capacity 120 kA  
Usable for size/applications industrial  
Standard/Approval IEC  
Shapes square body with knife blade contacts  
Standards/Regulations IEC 60269-2 fuse system A  
DIN 43620  
VDE 0636-2  
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected] [AFZ800015]) Construction size NH01 Rated current 10 A Rated voltage 500 V Voltage type AC Rated switching capacity 120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) Yes

ETIM for 10NHG01BI Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH01

Voltage type (EF000187)

AC

Rated current (EF0...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 10A 500V GG/GL SIZE 01 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.