

INDUSTRIAL COMPONENT DATA

NH FUSE 10A 500V GG/GL SIZE 01 10NHG01BI 0001664035

EATON ELECTRIC Fuse-link, LV, 10 A, AC 500 V, NH01, gL/g..

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 10A 500V GG/GL SIZE 01



Manufacturer	EATON - MOELLER
MPN / Reference	NH FUSE 10A 500V GG/GL SIZE 01
Catalog number	0001664035
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-73580A4243
Generated	2026-08-06

Product Overview

Fuse-link, LV, 10 A, AC 500 V, NH01, gL/gG, IEC, dual indicator, live gripping lugs

NH FUSE 10A 500V GG/GL SIZE 01

Fuse-link, low voltage, 10 A, AC 500 V, 120 kA, NH01, gL/gG, IEC, dual indicator, insulated gripping lugs

Fuse, Fuse-link, low voltage, 10 A, AC 500 V, NH01, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 10 A, AC 500 V, 120 kA, NH01, gL/gG, IEC, dual indicator, insulated gripping lugs
Fuse, Fuse-link, low voltage, 10 A, AC 500 V, NH01, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application low voltage
Rated current [I]_n 10 A
Rated voltage AC 500 V
Construction size NH01
Utilization category gL/gG
Status indicator dual indicator
Description insulated gripping lugs
Breaking Capacity 120 kA
Usable for size/applications industrial
Standard/Approval IEC
Shapes square body with knife blade contacts
Standards/Regulations IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size NH01 Rated current 10 A Rated voltage 500 V Voltage type AC Rated switching capacity 120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) Yes

ETIM for 10NHG01BI Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH01

Voltage type (EF000187)

AC

Rated current (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 10A 500V GG/GL SIZE 01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.