

## INDUSTRIAL COMPONENT DATA

# NH FUSE 32A 500V GL/GG SIZE 01 32NHG01BI EATON

## ELECTRIC Fuse-link, LV, 32 A, AC 500 V, NH01, gL/gG, IEC, dua..

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 32A 500V GL/GG SIZE 01



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | EATON - MOELLER                |
| MPN / Reference | NH FUSE 32A 500V GL/GG SIZE 01 |
| Catalog number  | 32NHG01BI                      |
| Category        | Low Voltage HRC fuse           |
| Minimum order   | 3 Pcs                          |
| Document ID     | EO-B3EEDB5D4D                  |
| Generated       | 2026-08-06                     |

### Product Overview

Fuse-link, LV, 32 A, AC 500 V, NH01, gL/gG, IEC, dual indicator, insulated gripping lugs

NH FUSE 32A 500V GL/GG SIZE 01

Fuse-link, low voltage, 32 A, AC 500 V, 120 kA, NH01, gL/gG, IEC, dual indicator, insulated gripping lugs

Fuse, Fuse-link, low voltage, 32 A, AC 500 V, NH01, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

### Additional Product Information

Fuse-link, low voltage, 32 A, AC 500 V, 120 kA, NH01, gL/gG, IEC, dual indicator, insulated gripping lugs  
Fuse, Fuse-link, low voltage, 32 A, AC 500 V, NH01, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2, Breaking Capacity 120 kA  
Delivery program

Product rangeFuseBasic functionFuse-linkField of applicationlow voltageRated current [I]<sub>N</sub>32 ARated voltageAC 500 VConstruction sizeNH01Utilization categorygL/gGStatus indicatordual indicatorDescriptioninsulated gripping lugsBreaking Capacity120 kAusable for size/applicationsindustrialStandard/ApprovalIECShapesquare body with knife blade contactsStandards/RegulationsIEC 60269-2 fuse system A

DIN 43620

VDE 0636-2 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]) [AFZ800015]) Construction size NH01 Rated current 32 A Rated voltage 500 V Voltage type AC Rated switching capacity 120 kA Utilization category GL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) Yes

ETIM for 32NHG01BI Circuit breakers and fuses (EC000055)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

NH01

Voltage type (EF000187)

AC

Rated current (EF0...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 32A 500V GL/GG SIZE 01 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.