

INDUSTRIAL COMPONENT DATA

NHI-B-11-PKZ0 208277 Y7-208277 EATON ELECTRIC Standard auxiliary contact, 1N/O+1N/C, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: NHI-B-11-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	NHI-B-11-PKZ0
Catalog number	Y7-208277
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-AE1B7DF24B
Generated	2026-08-06

Product Overview

Standard auxiliary contact, 1N/O+1N/C, screw connection

NHI-B-11-PKZ0

Eaton Moeller® series NHI Standard auxiliary contact, 1 N/O, 1 NC, Can be fitted to the front, Screw terminals

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with:

PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series NHI Accessory Standard auxiliary contact Catalog Number 208277 Model Code NHI-B-11-PKZ0 EAN 4015082082772 Product Length/Depth 12 mm Product Height 35 mm Product Width 45 mm Product Weight 0.015 kg Certifications CE

CSA File No.: 165628

CSA

CSA Class No.: 3211-05

UL 508

IEC/EN 60947-4-1

UL File No.: E36332

CSA-C22.2 No. 14

UL

UL Category Control No.: NLRV Features & Functions

Electric connection type Screw connection General

Lifespan, electrical 100,000 Operations Lifespan, mechanical 100,000 Operations Model Top mounting Mounting method Front fastening Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 4000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 1.5 mm² Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 1 A Rated operational current (Ie) at DC-13, 24 V 2 A Rated operational voltage (Ue) at AC - max 440 V Rated operational voltage (Ue) at DC - max 250 V Safe isolation 440 V, Between auxiliary contacts and main contacts, According to EN 61140 Short-circuit protection rating without welding 10 A gG/gL, Fuse, Auxiliary contacts Contacts

Control circuit reliability < 2 %, < 1 failure at 100,000,000 Operations (at Ue = 24 V DC, Umin = 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI-B-11-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.