

## INDUSTRIAL COMPONENT DATA

# NHI-B-11-PKZ0-PI 199326 Y7-199326 EATON ELECTRIC

## NHI-B-11-PKZ0-PI

Brand: EATON - MOELLER | Manufacturer Part Number: NHI-B-11-PKZ0-PI



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | EATON - MOELLER         |
| MPN / Reference | NHI-B-11-PKZ0-PI        |
| Catalog number  | Y7-199326               |
| Category        | Auxiliary contact block |
| Minimum order   | 5 Pcs                   |
| Document ID     | EO-E89222DB48           |
| Generated       | 2026-08-05              |

### Product Overview

NHI-B-11-PKZ0-PI

Eaton Moeller® series NHI Standard auxiliary contact, 1 N/O, 1 NC, Can be fitted to the front, Push in terminals  
Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with:  
PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Circuit Breakers PKZ

### Additional Product Information

## General specifications

Product Name Eaton Moeller® series NHI Accessory Standard auxiliary contact Catalog Number 199326 Model Code  
NHI-B-11-PKZ0-PI EAN 4015081974108 Product Length/Depth 35 mm Product Height 15 mm Product Width 45 mm

Product Weight 0.011 kg Compliances CE Marked

RoHS conform Certifications CSA File No.: 165628

CSA Class No.: 3211-05

UL File No.: E36332

UL Category Control No.: NLRV

UL 508

CE marking

CSA-C22.2 No. 14

IEC 60947-4-1

UL

**CSA Features & Functions**

Electric connection type Spring clamp connection Features Interlocked opposing contacts General

Lifespan, electrical 50,000 Operations Lifespan, mechanical 100,000 Operations Model Top mounting Mounting method

Front fastening Overvoltage category III Pollution degree 3 Rated impulse withstand voltage (Uimp) 4000 V AC Used with

Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (flexible with ferrule) 1 x (0.5 - 1) mm<sup>2</sup>, auxiliary terminals2 x (0.5 - 1) mm<sup>2</sup>, auxiliary terminals Terminal capacity (flexible) 0.5 - 1.5 mm<sup>2</sup>2 x (0.5 - 1.5) mm<sup>2</sup> Terminal capacity (solid) 0.5 - 1.5 mm<sup>2</sup> Terminal capacity (solid/stranded AWG) 20 - 14 Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 0.5 A Rated operational current (Ie) at DC-13, 24 V 1 A Rated operational voltage (Ue) at AC - max 440 V Rated operational voltage (Ue) at DC - max 250 V Safe isolation....

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / NHI-B-11-PKZ0-PI with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.