

INDUSTRIAL COMPONENT DATA

NHI-E-10-PKZ0-C-GVP 120945 EATON ELECTRIC Standard auxiliary contact, 1N/C with spring clamp connection, lar..

Brand: EATON - MOELLER | Manufacturer Part Number: NHI-E-10-PKZ0-C-GVP



Manufacturer	EATON - MOELLER
MPN / Reference	NHI-E-10-PKZ0-C-GVP
Catalog number	120945
Category	Auxiliary contact block
Minimum order	100 Pcs
Document ID	EO-EF9230F3FB
Generated	2026-08-06

Product Overview

Standard auxiliary contact, 1N/C with spring clamp connection, large packaging

Front Auxiliary Contact 1 NO Snap-On Connection Large Packaging

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, For use with: PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Motor-protective circuit-breakers PKZ (Accessories)
--------------	---

Additional Product Information

Standard auxiliary contact, 1N/C with spring clamp connection, large packaging Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, For use with: PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE Delivery program

Product range Accessories Accessories Standard auxiliary contact Can be fitted to the front

Terminal designation differs to that of an auxiliary contact that can be fitted to the side Contacts N/O = Normally open 1 N/O Contact diagram Contact sequence Connection technique Spring-loaded terminals For use with PKZ0(4) standard auxiliary contacts For use with PKZM01

PKZM0

PKZM4

PKZM0-T

PKM0

PKE Notes Can be fitted to:

Motor protective circuit-breaker

Transformer-protective circuit-breaker

Motor protective circuit breaker for starter combinations

(From serial number 01)

Cannot be used for motor starter combinations type MSC...

45 mm (PKZM0 and PKZM01) or 55 mm (PKZM4) widths of the motor-protective circuit-breakers remain unchanged.

Technical data

Auxiliary contacts Rated impulse withstand voltage [Uimp] 4000 V AC Overvoltage category/pollution degree III/3 Rated operational voltage [Ue] [Ue] 440 V AC Rated operational voltage [Ue] [Ue] 250 V DC Safe isolation to EN 61140 Between auxiliary contacts and main contacts 690 V AC Rated operational current [Ie] AC-15220 - 240 V [Ie] 1 A Rated operational current [Ie] DC-13 L/R - 100 ms 24 V [Ie] 2 A Lifespan Lifespan, mechanical [Operations] > 0.1 x 10⁶ Lifespan Lifespan, electrical [Operations] 0.1 x 10⁶ Control circuit reliabi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI-E-10-PKZ0-C-GVP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.